

SITOP PSU100M/1AC/24VDC/40A

SITOP PSU100M 40 A stabilized power supply input: 120/230 V AC output: 24 V DC/40 A !!!product phase-out!!!! successor: 6EP3337-8SB00-0AY0



input

type of the power supply network	1-phase AC
supply voltage at AC	Set by means of wire jumper on the device; starting from $V_{in} > 95/190$ V
supply voltage	120 V/230 V
input voltage 1 at AC	85 ... 132 V
input voltage 2 at AC	176 ... 264 V
wide range input	No
overvoltage overload capability	$2.3 \times V_{in}$ rated, 1.3 ms
buffering time for rated value of the output current in the event of power failure minimum	20 ms
operating condition of the mains buffering	at $V_{in} = 230$ V
line frequency	50/60 Hz
line frequency	47 ... 63 Hz
input current	
• at rated input voltage 120 V	15 A
• at rated input voltage 230 V	8 A
current limitation of inrush current at 25 °C maximum	125 A
I _{2t} value maximum	26 A ² ·s
fuse protection type	Yes
fuse protection type in the feeder	Recommended miniature circuit breaker at 1-phase operation: 20 A characteristic C; required at 2-phase operation: circuit breaker 2-pole connected or circuit breaker 3RV2421-4BA10 (120 V) or 3RV2411-1JA10 (230 V)

output

voltage curve at output	Controlled, isolated DC voltage
output voltage at DC rated value	24 V
output voltage	
• at output 1 at DC rated value	24 V
output voltage adjustable	Yes; via potentiometer
adjustable output voltage	24 ... 28.8 V
relative overall tolerance of the voltage	3 %
relative control precision of the output voltage	
• on slow fluctuation of input voltage	0.1 %
• on slow fluctuation of ohm loading	0.1 %
residual ripple	
• maximum	100 mV
• typical	60 mV
voltage peak	
• maximum	200 mV
• typical	120 mV
display version for normal operation	Green LED for 24 V OK

type of signal at output	via signaling module (6EP1961-3BA10)	
behavior of the output voltage when switching on	Overshoot of Vout approx. 3 %	
response delay maximum	0.1 s	
voltage increase time of the output voltage		
• typical	50 ms	
output current		
• rated value	40 A	
• rated range	0 ... 40 A; +60 ... +70 °C: Derating 2.5%/K	
supplied active power typical	960 W	
short-term overload current		
• at short-circuit during operation typical	120 A	
duration of overloading capability for excess current		
• at short-circuit during operation	25 ms	
constant overload current		
• on short-circuiting during the start-up typical	46 A	
bridging of equipment	Yes; switchable characteristic	
number of parallel-switched equipment resources for increasing the power	2	
efficiency		
efficiency in percent	88 %	
power loss [W]		
• at rated output voltage for rated value of the output current typical	131 W	
closed-loop control		
relative control precision of the output voltage with rapid fluctuation of the input voltage by +/- 15% typical	1 %	
relative control precision of the output voltage load step of resistive load 50/100/50 % typical	2 %	
setting time		
• load step 50 to 100% typical	2 ms	
• load step 100 to 50% typical	2 ms	
setting time		
• maximum	5 ms	
protection and monitoring		
design of the overvoltage protection	< 35 V	
property of the output short-circuit proof	Yes	
design of short-circuit protection	Alternatively, constant current characteristic approx. 46 A or latching shutdown	
• typical	46 A	
enduring short circuit current RMS value		
• typical	46 A	
display version for overload and short circuit	LED yellow for "overload", LED red for "latching shutdown"	
safety		
galvanic isolation between input and output	Yes	
galvanic isolation	Safety extra-low output voltage Uout acc. to EN 60950-1 and EN 50178	
operating resource protection class	Class I	
leakage current		
• maximum	3.5 mA	
• typical	0.4 mA	
protection class IP	IP20	
EMC		
standard		
• for emitted interference	EN 55022 Class B	
• for mains harmonics limitation	-	
• for interference immunity	EN 61000-6-2	
standards, specifications, approvals		
certificate of suitability		
• CE marking	Yes	
• UL approval	Yes; cULus-Listed (UL 508, CSA C22.2 No. 107.1), File E197259	
• CSA approval	Yes; cULus-Listed (UL 508, CSA C22.2 No. 107.1), File E197259	
• UKCA marking	Yes	
• EAC approval	Yes	

• Regulatory Compliance Mark (RCM)	Yes
• NEC Class 2	No
• SEMI F47	Yes
type of certification	
• CB-certificate	No
MTBF at 40 °C	540 249 h
standards, specifications, approvals hazardous environments	
certificate of suitability	
• IECEx	No
• ATEX	No
• ULhazloc approval	No
• cCSAus, Class 1, Division 2	No
• FM registration	No
standards, specifications, approvals marine classification	
shipbuilding approval	No
Marine classification association	
• American Bureau of Shipping Europe Ltd. (ABS)	No
• French marine classification society (BV)	No
• Det Norske Veritas (DNV)	No
• Lloyds Register of Shipping (LRS)	No
standards, specifications, approvals Environmental Product Declaration	
Environmental Product Declaration	Yes
global warming potential [CO2 eq]	
• total	4 146.1 kg
• during manufacturing	45.7 kg
• during operation	4 099 kg
• after end of life	0.65 kg
ambient conditions	
ambient temperature	
• during operation	0 ... 70; with natural convection
• during transport	-40 ... +85
• during storage	-40 ... +85
environmental category according to IEC 60721	Climate class 3K3, 5 ... 95% no condensation
connection method	
type of electrical connection	screw terminal
• at input	L, N, PE: 1 screw terminal each for 0.2 ... 4 mm ² single-core/finely stranded
• at output	+, -: 2 screw terminals each for 0.5 ... 10 mm ²
• for auxiliary contacts	-
mechanical data	
width x height x depth of the enclosure	240 x 125 x 125 mm
installation width x mounting height	240 mm x 225 mm
required spacing	
• top	50 mm
• bottom	50 mm
• left	0 mm
• right	0 mm
fastening method	Snaps onto DIN rail EN 60715 35x15
• DIN-rail mounting	Yes
• S7 rail mounting	No
• wall mounting	No
housing can be lined up	Yes
net weight	2.9 kg
accessories	
electrical accessories	Buffer module, signaling module
further information internet links	
internet link	
• to website: Industry Mall	https://mall.industry.siemens.com
• to web page: selection aid TIA Selection Tool	https://www.siemens.com/tstcloud
• to website: CAx-Download-Manager	https://siemens.com/cax
• to website: Industry Online Support	https://support.industry.siemens.com

additional information	
other information	Specifications at rated input voltage and ambient temperature +25 °C (unless otherwise specified)
security information	
security information	<p>Siemens provides products and solutions with industrial cybersecurity functions that support the secure operation of plants, systems, machines and networks. In order to protect plants, systems, machines and networks against cyber threats, it is necessary to implement – and continuously maintain – a holistic, state-of-the-art industrial cybersecurity concept. Siemens' products and solutions constitute one element of such a concept. Customers are responsible for preventing unauthorized access to their plants, systems, machines and networks. Such systems, machines and components should only be connected to an enterprise network or the internet if and to the extent such a connection is necessary and only when appropriate security measures (e.g. firewalls and/or network segmentation) are in place. For additional information on industrial cybersecurity measures that may be implemented, please visit www.siemens.com/cybersecurity-industry. Siemens' products and solutions undergo continuous development to make them more secure. Siemens strongly recommends that product updates are applied as soon as they are available and that the latest product versions are used. Use of product versions that are no longer supported, and failure to apply the latest updates may increase customer's exposure to cyber threats. To stay informed about product updates, subscribe to the Siemens Industrial Cybersecurity RSS Feed under https://www.siemens.com/cert. (V4.7)</p>

Classifications		Version	Classification
	eClass	14	27-04-07-01
	eClass	12	27-04-07-01
	eClass	9.1	27-04-07-01
	eClass	9	27-04-07-01
	eClass	8	27-04-90-02
	eClass	7.1	27-04-90-02
	eClass	6	27-04-90-02
	ETIM	9	EC002540
	ETIM	8	EC002540
	ETIM	7	EC002540
	IDEA	4	4130
	UNSPSC	15	39-12-10-04

Approvals Certificates	
General Product Approval	



[Manufacturer Declaration](#)

[Declaration of Conformity](#)



General Product Approval	Environment
--------------------------	-------------

[Miscellaneous](#)



last modified:

4/4/2025