



The Gar VFD69383x1NJN multiport/multiband antenna provides an excellent solution for public safety, transportation, and aftermarket fleet applications. Configured for one-port operation over the 3G/4G/5G/ISM/CBRS bands and a second port providing an active antenna for enabling GNSS global navigation services.

## FEATURES AND BENEFITS

- One single-hole mount/fixing- reduces vehicle damage and the cost of installation
- Attractive IP67 low profile aerodynamic housing
- Multiband/Multiport operation LTE/GNSS navigation

## APPLICATIONS

- FirstNet/Public safety
- Transportation
- Aftermarket fleet
- 5G-ready
- Rugged LTE gateways
- Others

### ELECTRICAL SPECIFICATIONS

Antenna Model	VFD69383x1NJN								
Number of Ports	2 (1x – LTE, 1x – GNSS)								
Port Configuration	1x – 3G/4G/5G/ISM/CBRS (LTE/CELL)								
Operating Frequency (MHz)	698-806	824-894	880-960	1690-1880	1850-1990	1910-2180	2300-2500	2500-2700	3300-3800
Peak Gain* – Avg. (dBi)	0.9	1.7	1.9	3.9	3.5	2.9	3.9	5.2	5.3
Peak Gain* – Max (dBi)	1.3	2.0	2.0	4.3	3.8	3.8	5.1	5.5	7.0
VSWR** – Avg.	1.7	1.6	1.6	1.5	1.4	1.5	1.6	1.5	1.3
VSWR** – Max	2.5	2.0	2.0	2.0	2.0	2.1	2.0	2.0	2.0
Isolation LTE1 to GNSS (dB)	-41	-43	-42	-46	-53	-53	-57	-53	-39
Azimuth Plane 3 dB Beamwidth	360°, Omnidirectional								
Nominal Impedance (Ohms)	50								
Polarization	Linear Vertical								
Max Power - Ambient 25°C (W)	30 (LTE/CELL)								

**Notes:** (\*) – This parameter is based on a 30cm (1ft) cable length and 30cm (1ft) ground plane.

(\*\*) – This parameter is based on a 518cm (17ft) cable length and 30cm (1ft) ground plane.

Antenna specifications are subject to change according to the ground plane size.

### MECHANICAL SPECIFICATIONS

Dimensions – L x W x H – mm (inches)	179 x 63 x 48 (7.04 x 2.48 x 1.69)
Weight – kg (lbs.)	0.54 kg (1.2 lbs.)
Mounting	P-Mount
Cable Type	LMR 100- pigtails, LMR 195- jumper cables, Black
Color	Black or White
Radome Material	PC, UL94-V0
Baseplate Material	Aluminum

### ENVIRONMENTAL SPECIFICATIONS

Operating Environment	Outdoor Vehicle
Operating Temperature – °C (°F)	-30 to +70°C (-22 to +158°F)
Storage Temperature – °C (°F)	-40 to +85°C (-40 to +185°F)
Ingress Protection Rating	IP67
Rail Compliance Standards	EN61373 (Shock & Vibration), EN50155 (Temperature)
Material Substance Compliance	RoHS

### CONFIGURATIONS

PART NUMBER	CABLE LENGTH		CONNECTORS		COLOR
	PIGTAIL	JUMPER	LTE/CELL	GNSS	
VFD69383B1NJN-518Q	0.3 m (1 ft.)	4.9 m (16 ft)	SMA-male	SMA-male	Black
VFD69383W1NJN-518Q	0.3 m (1 ft.)	4.9 m (16 ft)	SMA-male	SMA-male	White


**GNSS ANTENNA SPECIFICATIONS**

Frequency of Operation (MHz)	1559 - 1606		
Band	BEIDOU	GPS	GLONASS
Frequency Band (MHz)	1561.098 ± 2.046	1575.42 ± 1.023	1602 ± 5
Antenna Gain (dBi)	3.7	4.7	5.6
LNA Gain, Typ. @ room temp. (dB)		28 ±3	
Noise Figure @ room temp., Max (dB)		≤ 2.5 @ 1575 MHz	
Max VSWR @ room temp.		2.0:1	
Polarization		RHCP	
Nominal Impedance		50 Ω	
DC Voltage (Vdc)		3.3	
Operating Supply Voltage (Vdc)		2.5 - 7.0	
Current Consumption, Max @ room temp mA)		8.5 ± 3 @ 3.0V	
Out-of-band Signal Rejection Min @ room temp (dBc)	80 (@698-960 MHz)	80 (@1428-2700 MHz)	70 (@4900-5800 MHz)
Input Max Power (dBm)		-10	
Cable Type		RG174, Black	


**PACKAGING INFORMATION**

PACKAGED DIMENSIONS	CARTON	MASTER CARTON	AIR PALLET	OCEAN PALLET
Number of Antennas	1	4	140	196
Height - mm (in.)	130 (5.12)	235 (9.25)	1335 (52.56)	1813 (71.38)
Length - mm (in.)	222 (8.74)	543 (21.38)	1200 (47.24)	1200 (47.24)
Width - mm (in.)	222 (8.74)	232 (9.13)	800 (31.5)	800 (31.5)
Shipping Weight - kg (lb.)	0.77 (1.7)	3.62 (7.98)	140 (309)	190 (419)


**MECHANICAL DRAWINGS**




## RADIATION PATTERNS – LTE ANTENNAS




RADIATION PATTERNS – LTE ANTENNAS



RADIATION PATTERNS – LTE ANTENNAS



RADIATION PATTERNS – LTE ANTENNAS



**RoHS**

Laird warrants to the original end user customer of its products that its products are free from defects in material and workmanship. Subject to conditions and limitations Laird will, at its option, either repair or replace any part of its products that prove defective because of improper workmanship or materials. This limited warranty is in force for the useful lifetime of the original end product into which the Laird product is installed. Useful lifetime of the original end product may vary but is not to exceed five (5) years from the original date of the end product purchase.

Any information furnished by Laird Inc. and its agents is believed to be accurate and reliable. All specifications are subject to change without notice. Responsibility for the use and application of Laird materials rests with the end user, since Laird and its agents cannot be aware of all potential uses. Laird makes no warranties as to the fitness, merchantability or suitability of any Laird materials or products for any specific or general uses. Laird shall not be liable for incidental or consequential damages of any kind. All Laird products are sold pursuant to the Laird Terms and Conditions of sale in effect from time to time, a copy of which will be furnished upon request.

© Copyright 2020 Laird Inc. All Rights Reserved. Laird, Laird Technologies, the Laird Logo, and other marks are trademarks or registered trademarks of Laird Inc. or an affiliate company thereof. Other product or service names may be the property of third parties. Nothing herein provides a license under any Laird or any third-party intellectual property rights.

