

Automotive Sealed Hand-Mated Connector Guide

molex

	Connector	Circuits	Conductor Wire Size	Current (Max.) Per Circuit	Sealing	Temperature	Vibration Class (USCAR-2)	Pitch
0.50mm Terminals								
	Mini50	1x2,1x4,1x10 (2x2, 2x8 <i>in development</i>)	0.13 - 0.35mm ²	4A	IP68 IP69K (with backshell)	-40° - 125°C	Class V1 Chassis	1.8mm
0.64mm Terminals								
	MX64	2-8	0.35 - 0.75mm ²	10A	IP67	-40° - 125°C	Class V1 Chassis	2.54mm
1.20mm Terminals								
	TAK120 (in Development)	24	0.35 - 0.75mm ²	12A	IP67 IP69K	-40° - 125°C	Class V1 Chassis	2.54mm
	MXP120	2-6	0.35 - 1.00mm ²	13A	IP69K	-40° - 150°C	Class V4 Powertrain	4.0mm
1.50mm Terminals								
	MX150	2-6 Single Row 4-20 Dual Row	0.35 - 2.0mm ²	22A	IP67 IP69K (with backshell)	-40° - 150°C	Class V4 Powertrain	3.5mm 5.0mm

Superior Terminal Technology > For Tomorrow's Vehicles

High Performance Sealing, Vibration, Thermal Management
Low Mate Force with High Mating Cycles
Clean Body Terminals Options
Mat-Seal and Cable-Seal Terminal Options
AK-Standard (Arbeitskreis) Terminal Cavity Options
USCAR Connector Interface Options



molex