

Featured Products



The industry's first* to support 1,000-device mesh networks

Wi-SUN FAN Wireless Communication Module

BP35C5

*ROHM January 2021 study

Enables configuration of 1,000-device Sub-GHz mesh networks

- Supports large-scale mesh networks ideal for smart cities
- Sub-GHz wireless provides long-distance communication with low power consumption

Robust transmission • Achieves high reliability wireless communication

- Integrated automatic communication path and channel hopping functions ensure stable, high reliability wireless transmission

Certified modules allow for quick and easy development


- Certification under both "Wi-SUN" and "FCC & Japan's Radio Law" significantly reduces customer development load, enabling immediate evaluation with comprehensive support



■ Wi-SUN FAN


• Large-Scale Mesh Networks

Automatic communication path optimization function achieves high reliability wireless transmission




• Channel Hopping

Improved resistance against noise and interference



• High Data Rate

Low power consumption minimizes radio wave interference



■ Usage Cases

• Smart Cities

Streetlamps
Traffic lights
Smart meters
Solar panels
Parking lots
Bicycle lots
Other infrastructure



• Smart Buildings

AC control
Lighting control
Building maintenance




• Smart Logistics


Automated warehouses
Forklifts
AGV (Automated Guided Vehicles)



■ Solutions for Large-Scale Systems (1,000 Devices)




■ Block Diagram



■ Wi-SUN Communication Modules Lineup

Part No.	Supply Voltage (V)	Wi-SUN Profile	Frequency (MHz)	Antenna	Mounting Type	Interface	Radio Law Compliance	Operating Temp (°C)	Size (mm)
BP35A1	2.7 to 3.6 (Single power supply)	B Route	922.5 to 927.5	Built-in	Connector	UART	ARIB STD-T108 (Japan)	-20 to +80	22.0×33.5×3.9
BP35C0	2.6 to 3.6 (Single power supply)	B Route/HAN	922.5 to 927.5	—	Surface mount	UART	ARIB STD-T108 (Japan)	-30 to +85	15.0×19.0×2.6
BP35C2	4.5 to 5.5 (Single power supply)	B Route/HAN	922.5 to 927.5	Built-in	USB	USB	ARIB STD-T108 (Japan)	-20 to +50	21.4×49.7×8.5
BP35C0-J11	2.6 to 3.6 (Single power supply)	B Route/Enhanced HAN	922.5 to 927.5	—	Surface mount	UART	ARIB STD-T108 (Japan)	-30 to +85	15.0×19.0×2.6
New BP35C5	2.6 to 3.6 (Single power supply)	FAN	902.0 to 928.0	—	Surface mount	UART	ARIB STD-T108 (Japan), FCC_15C (North America)	-30 to +85	15.0×19.0×2.6

■ Software Stack



■ Evaluation Board



ROHM
Co., Ltd.

21 Saini Mizonaki-cho, Ukyo-ku,
Kyoto 615-8585 Japan

www.rohm.com

The content specified herein is for the purpose of introducing ROHM's products (hereinafter "Products"). If you wish to use any such Product, please be sure to refer to the specifications, which can be obtained from ROHM upon request. Great care was taken in ensuring the accuracy of the information specified in this document. However, should you incur any damage arising from any inaccuracy or misprint of such information, ROHM shall bear no responsibility for such damage. The technical information specified herein is intended only to show the typical functions of and examples of application circuits for the Products. ROHM does not grant you, explicitly or implicitly, any license to use or exercise intellectual property or other rights held by ROHM and other parties. ROHM shall bear no responsibility whatsoever for any dispute arising from the use of such technical information. If you intend to export or ship overseas any Product or technology specified herein that may be controlled under the Foreign Exchange and the Foreign Trade Law, you will be required to obtain a license or permit under the Law.

The content specified in this document is correct as of January 1st, 2021.