

**Gold Bonding Wire (Au100) Gold 23um (0.9mil)****Product Highlights**

High Purity Gold > 99.99% (4N). Designed specifically for wire bonding. Gold bonding wire is used to connect electrical components in many industries, including electronics, aerospace and medicine. Gold bonding wire has excellent electrical conductivity, stability and resistance to corrosion. It is an important material in semiconductor and electronic device manufacturing. It is commonly used for wire bonding to electrically connect microchip semiconductor dies to the terminals of a chip package or directly to a substrate. Commonly used by integrated circuit (IC) packaging shops, research labs and advanced manufacturing facilities.

**Specifications**

Alloy:	Au100
Melting Point:	1,064°C (1,947°F)
Packaging:	Spool
Diameter:	23µm (0.9 mil)
Length:	100m (328 feet)
Shelf Life:	> 12 months
Purity:	4N (>99.99%)
Wire Weight:	805 mg

**Storage and Handling**

Store in a dry non-corrosive environment.

**Transportation**

This product has no shipping restrictions.

**Test Results**

Test J-STD-004 or other requirements as stated	Test Requirement	Result
Conflict Minerals Compliance	Electronic Industry Citizenship Coalition (EICC)	Compliant
REACH Compliance	Articles 33 and 67 of Regulation (EC) No 1907/2006	Compliant

**Conforms to the following Industry Standards:**

J-STD-006C, Amendments 1 &amp; 2 (Solder Alloys and Fluxed/Non-Fluxed Solders):

Yes

RoHS 3 Directive (EU) 2015/863:

Yes

**Chip Quik Gold Bonding Wire (Au100) Orderable Part Numbers**

Part Number	Gold (Au) Purity	Diameter	Length	Photo
CQB-AU100-20um	4N (>99.99%)	20µm (0.8 mil)	100m (328 feet)	
CQB-AU100-23um	4N (>99.99%)	23µm (0.9 mil)	100m (328 feet)	
CQB-AU100-25um	4N (>99.99%)	25µm (1.0 mil)	100m (328 feet)	