



Declaration of Conformity

Manufacturer:
CUI Inc.
15575 SW Sequoia Parkway, Suite 100
Portland, Oregon 97224

For the following equipment:

DC-DC Converter
CUI Series: PRC600
Models: 300 Vdc nominal input, see next page

This declaration of conformity is issued under the sole responsibility of the manufacturer.
The object of the declaration described above is in conformity with the relevant Union harmonization legislations and their amendments:

Low Voltage Directive 2014/35/EU

EMC Directive 2014/30/EU

RoHS Directive 2011/65/EU and (EU) 2015/863

References to the relevant harmonized standards used, including the date of the standard, or references to the other technical specifications, including the date of the specification, in relation to which conformity is declared:

Health & Safety EN 62368-1:2014+A11:2017

EMC EN 55032:2015+A11:2020; EN 55035:2017+A11:2020

RoHS EN IEC 63000:2018

Note: These component level power supplies are intended exclusively for inclusion within other equipment. Protection against electric shock and Electromagnetic Compatibility (EMC) must be checked when the equipment is built-in a completed product or forms a part of a complete system.



(manufacturer)

Link Lu
Product Compliance Specialist

Shenzhen, China

(place)

08/20/2024

(date)



(manufacturer)

Editha Vergara
Global Director, Safety, Environmental

Portland, Oregon, USA

(place)

08/20/2024

(date)

MODEL LIST

PRC600-300-SXX (where XX = 12, 24, 48 denote output voltage)

Model	Input voltage (typ.) Vdc	Input voltage (range) Vdc	Output voltage (Vdc)
PRC600-300-S12	300	180-400	12
PRC600-300-S24	300	180-400	24
PRC600-300-S48	300	180-400	48

PRC600-300-SXXN (where XX = 12, 24, 48 denote output voltage)

Model	Input voltage (typ.) Vdc	Input voltage (range) Vdc	Output voltage (Vdc)
PRC600-300-S12N	300	180-400	12
PRC600-300-S24N	300	180-400	24
PRC600-300-S48N	300	180-400	48

Model Naming Configuration

PRC600	-	300	-	S	XX	X
I	-	II	-	III	IV	V

- I - Base Number: PRC600
- II - Nom. Input Voltage: 300 = 300 Vdc
- III - Output: S = single
- IV - Output Voltage: 12 = 12 V; 24 = 24 V; 48 = 48 V
- V - Remote ON/OFF CTRL: Blank = Positive Logic; N = Negative Logic

REVISION HISTORY

rev.	description	date
1.0	initial release	08/20/24

The revision history provided is for informational purposes only and is believed to be accurate.