



EC3SAW8 Series

Application Note V10 August 2025

ISOLATED DC-DC CONVERTER

EC3SAW8 SERIES

APPLICATION NOTE



Approved By:

Department	Approved By	Checked By	Written By
Research and Development Department	Ovid	Zhu Hai	Fei
		Yang	
Quality Assurance Department	Benny	JoJo	



EC3SAW8 Series

Application Note V10 August 2025

Contents

1. Introduction	3
2. Pin Function Description	3
3. Connection for Standard Use.....	4
4. Test Set-Up.....	4
5. Recommend Layout, PCB Footprint and Soldering Information.....	4
6. Features and Functions	5
6.1 <i>UVLO (Under Voltage Lock Out)</i>	5
6.2 <i>Over Current/Short Circuit Protection</i>	5
6.3 <i>Remote On/Off</i>	5
7. Input/Output Considerations	6
7.1 <i>Input Capacitance at the Power Module</i>	6
7.2 <i>Output Ripple and Noise</i>	6
7.3 <i>Output Capacitance</i>	6
8. Thermal Design.....	7
8.1 <i>Operating Temperature Range</i>	7
8.2 <i>Convection Requirements for Cooling</i>	7
8.3 <i>Thermal Considerations</i>	7
8.4 <i>Power Derating</i>	7
9. Safety & EMC	8
9.1 <i>Input Fusing and Safety Considerations</i>	8
9.2 <i>EMC Considerations</i>	8




EC3SAW8 Series

Application Note V10 August 2025

1. Introduction

The EC3SAW8 series offer 2.3-3 watts of output power in a 0.86x0.36x0.44 inches SIP-8 plastic packages. The EC3SAW8 series has a 8:1 wide input voltage range of 9-75VDC and provides a precisely regulated output. This series has features such as high efficiency, 3000VDC of isolation and allows an ambient operating temperature range of -40°C to 105°C with de-rating. The features include short circuit protection and Negative remote **on/off** control. All models are very suitable for distributed power architectures, telecommunications, battery operated equipment and industrial applications.

2. Pin Function Description



Single Output

No	Label	Function	Description	Reference
1	-Vin	-V Input	Negative Supply Input	Section 7.1
2	+Vin	+V Input	Positive Supply Input	Section 7.1
3	R.C	Remote On/Off	External Remote On/Off Control	Section 6.3
6	+Vout	+V Output	Positive Power Output	Section 7.2/7.3
7	-Vout	-V Output	Negative Power Output	Section 7.2/7.3
8	N.C	NC	No Connection with Pin	--

Dual Output

No	Label	Function	Description	Reference
1	-Vin	-V Input	Negative Supply Input	Section 7.1
2	+Vin	+V Input	Positive Supply Input	Section 7.1
3	R.C	Remote On/Off	External Remote On/Off Control	Section 6.3
6	+Vout	+V Output	Positive Power Output	Section 7.2/7.3
7	Com	Common	Common Power Output	Section 7.2/7.3
8	-Vout	-V Output	Negative Power Output	Section 7.2/7.3




EC3SAW8 Series

Application Note V10 August 2025

3. Connection for Standard Use

The connection for standard use is shown below. External output capacitors (C1, C2) are recommended to reduce output ripple and noise.



Symbol	Component	Reference
F1, TVS	Input fuse, TVS	Section 9.1
C1, C2	External capacitor to reduce output ripple and noise	Section 7.2
Noise Filter	External input noise filter	Section 9.2
Remote On/Off	External remote on/off control	Section 6.3

4. Test Set-Up

The basic test set-up to measure parameters such as efficiency and load regulation is shown below. When testing the modules under any transient conditions please ensure that the transient response of the source is sufficient to power the equipment under test. We can calculate:

- Efficiency
- Load regulation and line regulation

The value of efficiency is defined as:

$$\eta = \frac{V_o \times I_o}{V_{in} \times I_{in}} \times 100\%$$

Where:

V_o is output voltage

I_o is output current

V_{in} is input voltage

I_{in} is input current

The value of load regulation is defined as:

$$\text{Load reg.} = \frac{V_{FL} - V_{NL}}{V_{NL}} \times 100\%$$

Where:

V_{FL} is the output voltage at full load

V_{NL} is the output voltage at no load


The value of line regulation is defined as:

$$\text{Line reg.} = \frac{V_{HL} - V_{LL}}{V_{LL}} \times 100\%$$

Where:

V_{HL} is the output voltage of maximum input voltage at full load


V_{LL} is the output voltage of minimum input voltage at full load



EC3SAW8 Series Test Setup

5. Recommend Layout, PCB Footprint and Soldering Information

The system designer or end user must ensure that metal and other components in the vicinity of the converter meet the spacing requirements for which the system is approved. Low resistance and inductance PCB layout traces are the norm and should be used where possible. Due consideration must also be given to proper low impedance tracks between power module, input and output grounds. The recommended footprints and soldering profiles are shown below.



Note: Dimensions are in inches [millimeters]




EC3SAW8 Series

Application Note V10 August 2025

Clean the soldered side of the module with a brush, prevent liquid from getting into the module. Do not clean by soaking the module into liquid. Do not allow solvent to come in contact with product labels or resin case as this may change the color of the resin case or cause deletion of the letters printed on the product label. After cleaning, dry the modules well.


The suggested soldering iron is $420 \pm 10^\circ\text{C}$ for up to 4-10 seconds (less than 90W) used in double PCB and multilayer PCB, the other one is $385 \pm 10^\circ\text{C}$ for up to 2-6 seconds (less than 90W) used in the single PCB. Furthermore the recommended soldering profile is shown below.



6. Features and Functions



6.1 UVLO (Under Voltage Lock Out)

Input under voltage lockout is standard on the EC3SAW8 series unit. The unit will shut down when the input voltage drops below a lower threshold, and the unit will operate when the input voltage goes above the upper threshold.



6.2 Over Current/Short Circuit Protection

All models have internal over current and continuous short circuit protection. The unit operates normally once the fault condition is removed. At the point of current limit inception, the converter will go into hiccup mode protection.



6.3 Remote On/Off

The remote **on/off** input feature of the converter allows external circuitry to turn the converter on or off. Active high remote **on/off** is available as standard. The converter is turned on if the remote **on/off** pin is open circuit. Supplying the **on/off** pin at 0 to 1.2Vdc will turn the converter off. The signal level of the **on/off** pin is defined with respect to ground. If not using the **on/off** pin, leave the pin open (module will be on).

Logic State (Pin 3)	Positive Logic
Open	Module on
Logic Low	Module off




EC3SAW8 Series

Application Note V10 August 2025

7. Input/Output Considerations


7.1 Input Capacitance at the Power Module

The converters must be connected to low AC source impedance. To avoid problems with loop stability source inductance should be low. Also, the input capacitors (C_{in}) should be placed close to the converter input pins to de-couple distribution inductance. However, the external input capacitors are chosen for suitable ripple handling capability. Low ESR capacitors are good choice. Circuit as shown as below represents typical measurement methods for reflected ripple current. C_1 and L_1 simulate a typical DC source impedance. The input reflected-ripple current is measured by current probe to oscilloscope with a simulated source inductance (L_1).




L1: 12uH
 C1: None
 Cin: None

7.2 Output Ripple and Noise



Note:
 C1: None
 C2: None

EC3SAW8 Single Output Module



Note:
 C1 & C3: None
 C2 & C4: None


EC3SAW8 Dual Output Module

Output ripple and noise measured across input/output. A 20 MHz bandwidth oscilloscope is normally used for the measurement.


The conventional ground clip on an oscilloscope probe should never be used in this kind of measurement. This clip, when placed in a field of radiated high frequency energy, acts as an antenna or inductive pickup loop, creating an extraneous voltage that is not part of the output noise of the converter.



Another method is shown in below in case of coaxial-cable/BNC is not available. The noise pickup is eliminated by pressing scope probe ground ring directly against the $-V_{out}$ terminal while the tip contacts the $+V_{out}$ terminal. This makes the shortest possible connection across the output terminals.



Using Probe to Measure Output Ripple and Noise



7.3 Output Capacitance

The EC3SAW8 series converters provide unconditional stability with or without external capacitors. For good transient response, low ESR output capacitors should be located close to the point of load ($<100mm$). PCB design emphasizes low resistance and inductance tracks in consideration of high current applications. Output capacitors with their associated ESR values have an impact on loop stability and bandwidth. Cincon's converters are designed to work with load capacitance to see technical specifications.



EC3SAW8 Series

Application Note V10 August 2025

8. Thermal Design

8.1 Operating Temperature Range

The EC3SAW8 series converters can be operated within a wide case temperature range of -40°C to 110°C. Consideration must be given to the derating curves when ascertaining maximum power that can be drawn from the converter. The maximum power drawn from models is influenced by usual factors, such as:

- Input voltage range
- Output load current
- Forced air or natural convection

8.2 Convection Requirements for Cooling

To predict the approximate cooling needed for the 0.86"×0.36" module, refer to the power derating curves in **datasheet**. These derating curves are approximations of the ambient temperatures and airflows required to keep the power module temperature below its maximum rating. Once the module is assembled in the actual system, the module's temperature should be monitored to ensure it does not exceed 110°C as measured at the center of the top of the case (thus verifying proper cooling).

8.3 Thermal Considerations

The power module operates in a variety of thermal environments; however, sufficient cooling should be provided to help ensure reliable operation of the unit. Heat is removed by conduction, convection, and radiation to the surrounding environment. The example is presented in **datasheet**. The power output of the module should not be allowed to exceed rated power ($V_{o_set} \times I_{o_max.}$).

8.4 Power Derating

The operating case temperature range of EC3SAW8 series is -40°C to +105°C. When operating the EC3SAW8 series, proper derating or cooling is needed. The maximum case temperature under any operating condition should not exceed 110°C (refer to **datasheet**).




EC3SAW8 Series

Application Note V10 August 2025

9. Safety & EMC

9.1 Input Fusing and Safety Considerations

The EC3SAW8 series converters have no internal fuse. In order to achieve maximum safety and system protection always use an input line fuse. We recommended a fast acting fuse 1A for all models. It is recommended that the circuit have a transient voltage suppressor diode (TVS) across the input terminal to protect the unit against surge or spike voltage and input reverse voltage (as shown).



The external TVS & input capacitor (Cin) is required if EC3SAW8 series has to meet EN 61000-4-4 & EN 61000-4-5


Cin: None

TVS: a SMCJ78A transient voltage suppressor is recommended

9.2 EMC Considerations

EMI Test standard: EN 55032 Conducted & Radiated Emission

Test Condition: Input Voltage: Nominal, Output Load: Full Load



EC3SAW8 Single Output Module

EC3SAW8 Dual Output Module

Model Number	EN 55032	Conduction		Radiation	
		C1	L1	C1	L1
EC3SAW8 Series	Class A	2.2uF/100V X7R 10% R TDK 1210	15uH	NC	Short
	Class B	2.2uF/100V X7R 10% R TDK 1210	68uH	2.2uF/100V X7R 10% R TDK 1210	68uH

Note:

C1: 1210 X7R ceramic capacitor

L1: HPIF0402-150M for Class A or HPIF0402-680M for Class B




EC3SAW8 Series

Application Note V10 August 2025


Conducted Emission Class B ($V_{in}=24V_{dc}$):

EC3SAW8-48S33P

Line




Neutral




EC3SAW8-48S05P

Line




Neutral




EC3SAW8-48S12P

Line




Neutral




EC3SAW8-48S15P

Line



Neutral






EC3SAW8 Series


Application Note V10 August 2025

EC3SAW8-48D05P

Line




Neutral




EC3SAW8-48D12P

Line




Neutral




EC3SAW8-48D15P

Line



Neutral






EC3SAW8 Series

Application Note V10 August 2025


Conducted Emission Class B ((V_{in}=48V_{dc}):

EC3SAW8-48S33P

Line




Neutral




EC3SAW8-48S05P

Line




Neutral




EC3SAW8-48S12P

Line




Neutral




EC3SAW8-48S15P

Line



Neutral






EC3SAW8 Series


Application Note V10 August 2025

EC3SAW8-48D05P

Line




Neutral




EC3SAW8-48D12P

Line




Neutral




EC3SAW8-48D15P

Line



Neutral






EC3SAW8 Series

Application Note V10 August 2025


Radiation Emission Class B ($V_{in}=24V_{dc}$):

EC3SAW8-48S33P

Horizontal




Vertical




EC3SAW8-48S05P

Horizontal




Vertical




EC3SAW8-48S12P

Horizontal




Vertical




EC3SAW8-48S15P

Horizontal



Vertical






EC3SAW8 Series


Application Note V10 August 2025

EC3SAW8-48D05P

Horizontal




Vertical




EC3SAW8-48D12P

Horizontal




Vertical




EC3SAW8-48D15P

Horizontal



Vertical






EC3SAW8 Series

Application Note V10 August 2025


Radiation Emission Class B ($V_{in}=48V_{dc}$):

EC3SAW8-48S33P

Horizontal




Vertical




EC3SAW8-48S05P

Horizontal




Vertical




EC3SAW8-48S12P

Horizontal




Vertical




EC3SAW8-48S15P

Horizontal



Vertical






EC3SAW8 Series


Application Note V10 August 2025

EC3SAW8-48D05P

Horizontal




Vertical




EC3SAW8-48D12P

Horizontal




Vertical




EC3SAW8-48D15P

Horizontal



Vertical



CINCON ELECTRONICS CO., LTD.

Headquarters:

14F, No.306, Sec.4, Hsin Yi Rd.
Taipei, Taiwan
Tel: 886-2-27086210
Fax: 886-2-27029852
E-mail: sales@cincon.com.tw
Web Site: <https://www.cincon.com>

Factory:

No. 8-1, Fu Kung Rd.
Fu Hsing Industrial Park
Fu Hsing Hsiang,
ChangHua Hsien, Taiwan
Tel: 886-4-7690261
Fax: 886-4-7698031

Cincon North America:

1655Mesa Verde Ave. Ste 180
Ventura, CA93003
Tel: 805-639-3350
Fax: 805-639-4101
E-mail: info@cincon.com