



## DESCRIPTION

The EV183-J-00A is an evaluation board designed to demonstrate the capabilities of the MP183. The MP183 is a primary-side constant voltage regulator that provides accurate constant voltage (CV) regulation without an optocoupler. It supports buck, buck-boost, boost, and flyback topologies.

The EV183-J-00A is designed as a buck application. It typically outputs 3W with a 12V/250mA load from an 85V<sub>AC</sub> to 265V<sub>AC</sub> input.

The EV183-J-00A achieves low standby power consumption and high efficiency under full-load and light-load conditions.

The EV183-J-00A can pass the IEC 61000-4-5 surge immunity test and meets EN55022/CISPR 22 Class B standards for conducted emissions. The radiated emissions performance is also improved.

Full protection features include thermal shutdown (TSD), V<sub>CC</sub> under-voltage lockout (UVLO), brown-in (B/I), overload protection (OLP), short-circuit protection (SCP), and open-loop detection (OLD).

## PERFORMANCE SUMMARY

Specifications are at T<sub>A</sub> = 25°C, unless otherwise noted.

Parameters	Conditions	Value
Input voltage (V <sub>IN</sub> ) range		85V <sub>AC</sub> to 265V <sub>AC</sub>
Output voltage (V <sub>OUT</sub> )	V <sub>IN</sub> = 85V <sub>AC</sub> to 265V <sub>AC</sub> , I <sub>OUT</sub> = 0A to 0.25A	12V
Maximum output current (I <sub>OUT</sub> )	V <sub>IN</sub> = 85V <sub>AC</sub> to 265V <sub>AC</sub>	0.25A
Typical efficiency	V <sub>IN</sub> = 230V <sub>AC</sub> , V <sub>OUT</sub> = 12V, I <sub>OUT</sub> = 0.25A	78.6%

**EVALUATION BOARD**

Top View



Bottom View

LxWxH (56mmx20mmx17mm)

Board Number	MPS IC Number
EV183-J-00A	MP183GJ

## QUICK START GUIDE

1. Preset the power supply input voltage ( $V_{IN}$ ) to be between 85V<sub>AC</sub> and 265V<sub>AC</sub>.
2. Turn off the power supply.
3. Connect the power supply terminals to:
  - a. Line terminal: L port
  - b. Neutral terminal: N port
4. Connect the load terminals to:
  - a. Positive (+): V<sub>OUT</sub>
  - b. Negative (-): GND
5. After making the connections, turn on the power supply. The device should start up automatically.




Figure 1: Measurement Equipment Set-Up

## EVALUATION BOARD SCHEMATIC








Figure 2: Evaluation Board Schematic

**EV183-J-00A BILL OF MATERIALS**

Qty	Ref	Value	Description	Package	Manufacturer	Manufacturer PN
2	C1, C2	10µF	Electrolytic capacitor, 400V, 20%	DIP	Any	
1	C3	220pF	Ceramic capacitor, 50V, X7R	0603	Wurth	885012206079
1	C4	33pF	Ceramic capacitor, 50V, COG	0603	Murata	GRM1885C1H330JA01D
1	C5	2.2µF	Ceramic capacitor, 25V, X7S	0603	Murata	GRM188C71E225KE11D
1	C7	470µF	Electrolytic capacitor, 25V	DIP	YongMing	LKM_25V_470uF_8*11.5
1	C8	1µF	Ceramic capacitor, 25V, X7R	0603	Murata	GCM188R71E105KA64D
5	D1, D2, D4, D6, D7	1000V	Diode, 1A	DO-41	Diodes, Inc.	1N4007
1	D3	600V	Diode, 1A	DO-41	ST	STTH1R06
1	F1	10Ω	Fuse resistor, 5%, 1W	DIP	Yageo	FKN1WSJT-52-10R
1	L1	1mH	Inductor, 1000µH, 8Ω, 0.1A	DIP	Any	
1	L2	1mH	Inductor, 2.5Ω, 420mA	DIP	Wurth	744743102
1	R4	100kΩ	Film resistor, 1%	1206	Yageo	RC1206FR-07100KL
1	JR0	0Ω	Film resistor, 1%	1206	Yageo	RC1206FR-070RL
1	U1	MP183	12V, 0.25A, zero standby, primary-side regulator	TSOT23-5	MPS	MP183GJ

## EVB TEST RESULTS

Performance curves and waveforms are tested on the evaluation board.  $V_{IN} = 230V_{AC}$ ,  $V_{OUT} = 12V$ ,  $I_{OUT} = 0.25A$ ,  $T_A = 25^\circ C$ , unless otherwise noted.



### Note:


- 1) The test for standby power should be conducted after tens of minutes from start-up. In this scenario, the leakage current of the electrolytic capacitors tends to be low and stable. The test results may differ considering the consistency of the capacitor.

## EVB TEST RESULTS (*continued*)

Performance curves and waveforms are tested on the evaluation board.  $V_{IN} = 230V_{AC}$ ,  $V_{OUT} = 12V$ ,  $I_{OUT} = 0.25A$ ,  $T_A = 25^{\circ}C$ , unless otherwise noted.


### Thermal Performance

$V_{IN} = 85V_{AC}$ ,  $f_{SW} = 35.7kHz$




### Thermal Performance

$V_{IN} = 265V_{AC}$ ,  $f_{SW} = 38.5kHz$




### Conducted EMI

L Line




### Conducted EMI

N Line



### Radiated EMI

CND




## EVB TEST RESULTS (continued)

Performance curves and waveforms are tested on the evaluation board.  $V_{IN} = 230V_{AC}$ ,  $V_{OUT} = 12V$ ,  $I_{OUT} = 0.25A$ ,  $T_A = 25^{\circ}C$ , unless otherwise noted.


### Output Voltage Ripple

$V_{IN} = 230V_{AC}$ ,  $I_{OUT} = 250mA$




### Start-Up

$V_{IN} = 230V_{AC}$ ,  $I_{OUT} = 250mA$




### Shutdown

$V_{IN} = 230V_{AC}$ ,  $I_{OUT} = 250mA$




### OLP Entry and Recovery

$V_{IN} = 230V_{AC}$ ,  $I_{OUT} = 250mA$




### Open-Loop Entry and Recovery

$V_{IN} = 230V_{AC}$ ,  $I_{OUT} = 250mA$



### Load Transient

$V_{IN} = 230V_{AC}$ , from half load to full load



## SURGE PERFORMANCE

Performance curves and waveforms are tested on the evaluation board.  $V_{IN} = 230V_{AC}$ ,  $V_{OUT} = 12V$ ,  $I_{OUT} = 0.25A$ ,  $T_A = 25^\circ C$ , unless otherwise noted.

Surge Level (V)	Input Voltage (V <sub>AC</sub> )	Injection Location	Injection Phase (°)	Test Result (Pass/Fail)
1000	230	L to N	0	Pass
1000	230	L to N	90	Pass
1000	230	L to N	180	Pass
1000	230	L to N	270	Pass
-1000	230	L to N	0	Pass
-1000	230	L to N	90	Pass
-1000	230	L to N	180	Pass
-1000	230	L to N	270	Pass

## CIRCUIT DESCRIPTION

The EV183-J-00A is configured in a buck regulator topology, it uses primary-side control and indirect feedback which can mostly simplify the schematic and get a cost-effective BOM. It can also achieve constant-voltage (CV) control and acceptable regulation. The biggest highlight of the EV183-J-00A is zero low standby power, which makes it a good candidate for many auxiliary power supplies.

F1, a fusible resistor, is used to protect the circuit from component failure or some excessive short events. It can also restrain the inrush current.

C1, L1, and C2 compose the  $\pi$  filter to guarantee that the conducted EMI meets the EN55022 standard. C1 and C2 are also used for energy storage and protecting against line surges.

C3 is used to filter the noise on FB. C4 cancels out the delay induced by C3 and the internal resistor divider.

C5 and D4 are used for output voltage sample-holding and the VCC power supply. R1 and R2 are reserved as external dividers to tune the regulated voltage in the event of other output specification requirements.

D3 is the freewheeling diode. For universal voltage applications, use a diode with a 600V reverse-block voltage. An ultra-fast recovery diode is recommended to improve efficiency.

C7 and C8 are output capacitors for the 12V output. C7 should be a low-ESR electrolytic capacitor for a low output voltage ripple. C8 is a small ceramic capacitor that reduces high-frequency noise on the output. R4 is dummy load that lowers the output voltage of the 12V rail under no-load conditions.

## PCB LAYOUT




Figure 5: Top Layer




Figure 6: Bottom Layer

**REVISION HISTORY**

Revision #	Revision Date	Description	Pages Updated
1.0	9/4/2024	Initial Release	-

**Notice:** The information in this document is subject to change without notice. Please contact MPS for current specifications. Users should warrant and guarantee that third-party Intellectual Property rights are not infringed upon when integrating MPS products into any application. MPS will not assume any legal responsibility for any said applications.