

NEO-F10T module

u-blox F10 high accuracy timing module

Compact dual-band GNSS receiver with nanosecond-level timing accuracy

- Meets 5G time synchronization requirements on a global scale
- Unaffected by ionospheric errors
- Combines accurate timing with low power consumption
- Built-in security for highest robustness against malicious attacks
- Industry-standard compact NEO form factor – easy upgrade from NEO-M8T



Standard



Professional



Automotive

12.2 x 16.0 x 2.4 mm



Product description

The NEO-F10T timing module provides nanosecond-level timing accuracy to the most demanding infrastructure applications.

Thanks to the module's dual-band functionality, it can provide excellent timing accuracy without the need of an external GNSS correction service. Additionally, when within the operational area of a Satellite Based Augmentation System (SBAS), NEO-F10T offers the possibility to improve the timing performance by using the ionospheric corrections provided by the SBAS system.

As NEO-F10T supports all four global satellite constellations, it is ideal for global deployments with single HW SKU. The NEO-F10T module supports the L1/L5/E5a configuration.

NEO-F10T includes advanced security features such as secure boot, secure interfaces, and T-RAIM to provide the highest level timing integrity.

The module has a single RF input for all the GNSS bands and dual SAW filters for exceptional signal selectivity and out-of-band attenuation.

NEO-F10T is designed to meet the most stringent timing synchronization requirements in 5G mobile networks on a global scale. By significantly reducing the time error of the primary source of cellular network synchronization, the NEO-F10T module will help operators maximize the performance of their networks and so optimize the return on their investment in 5G communications.

u-blox modules are manufactured in IATF 16949 certified sites and are fully tested on a system level. Qualification tests are performed as stipulated in the ISO16750 standard: "Road vehicles – Environmental conditions and testing for electrical and electronic equipment".

NEO-F10T	
Grade	
Automotive	
Professional	•
Standard	
GNSS	
GPS / QZSS	•
GLONASS	•
Galileo	•
BeiDou	•
NavIC	•
Multi-band	L1/L5/E5a
Interfaces	
UART	1
Features	
Programmable (Flash)	•
Carrier phase output	•
Additional SAW	•
RTC crystal	•
Oscillator	T
Survey-in and fixed mode	•
Time pulse output	1
Time mark input	1
Power supply	
2.7 V – 3.6 V	•

T = TCXO

Features

Receiver type	u-blox F10 engine GPS L1C/A, L5 GAL E1B/C, E5a QZSS L1C/A, L5 NavIC L5 SBAS L1C/A: WAAS, EGNOS, L1Sb, GAGAN	GLO L1OF BDS B1C, B2a
Nav. update rate ¹	up to 10 Hz	
Position accuracy ²	Standalone	2.0 m CEP
Acquisition	Cold starts Aided starts Reacquisition	26 s 2 s 1 s
Sensitivity	Tracking and Nav. Reacquisition Hot starts Cold starts	-167 dBm -160 dBm -157 dBm -148 dBm
Assistance	AssistNow Online OMA SUPL and 3GPP compliant	
Oscillator	TCXO	
RTC crystal	Built-in	
Anti-jamming	Active CW detection and removal Dual onboard band pass filters	
Anti-spoofing	Advanced anti-spoofing algorithms	
Security	Secure boot Secure firmware update Configuration lock	
Memory	Flash	

1 The highest navigation rate can limit the number of supported constellations

2 Depends on atmospheric conditions, GNSS antenna, multipath conditions, satellite visibility, and geometry

Features - Timing

Timing accuracy	10 ns (1-sigma, clear sky, dual-band mode)
Time pulse frequency	0.25Hz – 25 MHz
Time pulse jitter	±8 ns
Time mark resolution	16 ns
Integrity reports	T-RAIM active, phase uncertainty Time pulse rate/duty-cycle, inter-constellation biases
Survey-in period	Configurable

Features - Raw data

Measurement data	Carrier phase, code phase and pseudo-range, Doppler on all signals
Message data	GPS, GLONASS, BeiDou, Galileo, QZSS, NavIC, SBAS

Package

24-pin LCC (Leadless Chip Carrier) 12.2 x 16.0 x 2.4 mm
--

Environmental data, quality and reliability

Operating temp.	-40 °C to +85 °C
Storage temp.	-40 °C to +85 °C
RoHS compliant (2015/863/EU)	
ETSI-RED compliant	
Qualification according to ISO 16750	
Manufactured and fully tested in IATF 16949 certified production sites	
High vibration and shock resistance	

Electrical data

Supply voltage	2.7 V to 3.6 V
Power consumption	19 mA @ 3.0 V (continuous)
Backup supply	1.65 V to 3.6 V

Interfaces

Serial interfaces	1 UART
Protocols	NMEA, UBX binary
Time pulse output	1
Time mark input	1

Support products

u-blox support products provide reference design, and allow efficient integration and evaluation of u-blox positioning technology.	
ANN-MB1	L1/L5 multi-band active GNSS antenna

Product variants

NEO-F10T-00B	u-blox F10 high accuracy timing module, with L1/L5/E5a bands
--------------	--

Further information

For contact information, see www.u-blox.com/contact-u-blox.

For more product details and ordering information, see the product data sheet.

Legal Notice:

u-blox or third parties may hold intellectual property rights in the products, names, logos and designs included in this document. Copying, reproduction, or modification of this document or any part thereof is only permitted with the express written permission of u-blox. Disclosure to third parties is permitted for clearly public documents only.

The information contained herein is provided "as is". No warranty of any kind, either express or implied, is made in relation to the accuracy, reliability, fitness for a particular purpose, or content of this document. This document may be revised by u-blox at any time. For most recent documents, please visit www.u-blox.com.