

# ST25DV-I2C SERIES

## Dynamic NFC tags NFC Forum Type 5 with optimized I2C



**Cost-effective NFC Forum Type 5 dynamic tags with quick firmware upgrade and write times as good as conventional EEPROM**

The ST25D family of dynamic NFC tags (ST25DV04KC, ST25DV16KC and ST25DV64KC) are ISO 15693 compliant NFC Forum Type 5 tags offering a wide range of features, including advanced I2C capabilities such as fast write.

The high-reliability EEPROM memory bank can be accessed either via low-power I2C interface or RF interface. An additional 256-Byte Fast Transfer Mode buffer enables rapid data transfer between the RF and I2C port. Other features include energy harvesting capability, RF status function, and 64-bit data password protection.

### KEY FEATURES & BENEFITS

- ISO 15693 NFC Forum Type 5
- I2C: 1MHz from 1.8 to 5.5V
- 4-, 16- and 64-kbit user EEPROM
- 256-Byte Fast Transfer Mode buffer
- 16-Byte page size for I2C write
- 64-bit unique identifier
- 64-bit passwords protection
- Energy harvesting
- Configurable Output signal (GPO)
- RF Field detect
- Configurable I2C address
- Several RF & I2C interrupts
- Low-power mode
- Industrial temperature range up to 125°C
- EEPROM endurance 1million write cycles
- EEPROM data retention of 40 years

### KEY BENEFITS

- Quick firmware upgrade
- Enables battery-less designs
- Improved user experience
- High-reliability EEPROM
- Flexible password protection scheme
- Simple and cost-effective
- Easy device calibration and product activation

### MAIN APPLICATIONS

- Lighting & Metering
- Industrial and Medical equipment
- Smart home
- Consumer electronics
- ESL (Electronic Shelf Label)
- Asset tracking and logistics

## Device summary

| Part number | RF Interface                  | Serial Interface | Memory size | Clock Frequency (MHz) | Data protection  | Supply (V) | Package                         | Energy Harvesting Output |
|-------------|-------------------------------|------------------|-------------|-----------------------|------------------|------------|---------------------------------|--------------------------|
| ST25DV04KC  | ISO 15693<br>NFC Forum Type 5 | I2C              | 4-Kbit      | 1                     | 64-bit passwords | 1.8 to 5.5 | S08, TSSOP8, FPN8, FPN12, WLCSP | Yes                      |
| ST25DV16KC  | ISO 15693<br>NFC Forum Type 5 | I2C              | 16-Kbit     | 1                     | 64-bit passwords | 1.8 to 5.5 | S08, TSSOP8, FPN12              | Yes                      |
| ST25DV64KC  | ISO 15693<br>NFC Forum Type 5 | I2C              | 64-Kbit     | 1                     | 64-bit passwords | 1.8 to 5.5 | S08, TSSOP8, FPN12              | Yes                      |

## Evaluation kits



ST25DV64KC-DISCO discovery kit

X-NUCLEO-NFC07A1 expansion board




ANT7-T-25DV64KC reference board

## Eco-System



### Support eco-system



© STMicroelectronics - June 2021 - Printed in the United Kingdom - All rights reserved  
 ST and the ST logo are registered and/or unregistered trademarks of STMicroelectronics International NV or its affiliates in the EU and/or elsewhere. In particular, ST and the ST logo are Registered in the US Patent and Trademark Office.  
 For additional information about ST trademarks, please refer to [www.st.com/trademarks](http://www.st.com/trademarks).  
 All other product or service names are the property of their respective owners.

