



# EV2174C-G-00A

## 4A, 5.5V, 1.1MHz Synchronous Step-Down Switcher Evaluation Board

### DESCRIPTION

The EV2174C-G-00A is used for demonstrating the performance of MPS's MP2174C, a low voltage high switching frequency step-down switcher with built in power MOSFETs. MP2174C provides up to 4A highly efficient output with constant-on-time control for fast loop response. The output voltage can be regulated as low as 0.6V.

High power efficiency over a wide load range is achieved by scaling down the switching frequency at light load to reduce the switching related loss by constant on time control. Short circuit and thermal shutdown provides reliable, fault-tolerant operation.

MP2174C is available in QFN12 (2x2mm) package.

### ELECTRICAL SPECIFICATION

| Parameter      | Symbol    | Value    | Units |
|----------------|-----------|----------|-------|
| Input Voltage  | $V_{IN}$  | 2.7– 5.5 | V     |
| Output Voltage | $V_{OUT}$ | 1.2      | V     |
| Output Current | $I_{OUT}$ | 4        | A     |

### FEATURES


- Forced PWM Mode Operation
- Wide 2.7V to 5.5V Operating Input Range
- Output Voltage as Low as 0.6V
- 4A Output Current
- 35mΩ and 18mΩ Internal Power MOSFET
- 1.1MHz Frequency
- 100% Duty cycle in Dropout
- 0.5ms Internal Soft-Start Time
- EN and Power Good for Power Sequencing
- Auto Discharge at Power-off
- Short Circuit Protection with Hiccup Mode
- Available in a QFN12 (2x2mm) Package

### APPLICATIONS

- Storage Drives
- Portable/Handheld Devices
- PDAs
- DVD Drives
- Wireless/Networking Cards
- Low Voltage I/O System Power

All MPS parts are lead-free and adhere to the RoHS directive. For MPS green status, please visit MPS website under Quality Assurance. "MPS" and "The Future of Analog IC Technology" are Registered Trademarks of Monolithic Power Systems, Inc.


## EV2174C-G-00A EVALUATION BOARD




| Board Number  | MPS IC Number |
|---------------|---------------|
| EV2174C-G-00A | MP2174CGG     |

### Efficiency vs. Output Current

$V_{IN}=5V$ ,  $DCR=27m\Omega$



## EVALUATION BOARD SCHEMATIC



## EV2174C-G-00A BILL OF MATERIALS


| Qty | RefDes            | Value   | Description                             | Package     | Manufacturer | Manufacturer P/N   |
|-----|-------------------|---------|-----------------------------------------|-------------|--------------|--------------------|
|     | C1A,C2A,<br>C3,C4 | NS      |                                         |             |              |                    |
| 1   | C1                | 22µF    | Ceramic Cap., 10V, 20%, X5R             | 0805        | Taiyo Yuden  | LMK212BJ226MG-T    |
| 1   | C2                | 10µF    | Ceramic Cap., 6.3V, 10%, X5R            | 0805        | muRata       | GRM21BR70J106KE76L |
| 1   | L1                | 1.0µH   | Inductor, I <sub>S</sub> = 9A, DCR=27mΩ | SMD         | Würth        | 74437324010        |
|     | R1                | NS      |                                         |             |              |                    |
| 1   | R2                | 100k    | Film Res., 5%                           | 0603        | Yageo        | RC0603JR-07100KL   |
|     | R3                | NS      |                                         |             |              |                    |
| 2   | R4,R5             | 200k    | Film Res., 5%                           | 0603        | Yageo        | RC0603JR-07200KL   |
| 1   | U1                | MP2174C | Synchronous Step-Down switcher          | QFN12-2x2mm | MPS          | MP2174CGG          |

# TYPICAL PERFORMANCE CHARACTERISTICS

$V_{IN} = 5V$ ,  $V_{OUT} = 1.2V$ ,  $L = 1\mu H$ ,  $T_A = +25^\circ C$ , unless otherwise noted.


## Output Ripple

$V_{IN}=3.6V$ ,  $V_{OUT}=3.3V$ ,  $I_{OUT}=0A$




## Output Ripple

$V_{IN}=5V$ ,  $V_{OUT}=1.2V$ ,  $I_{OUT}=0A$




## Output Ripple

$V_{IN}=5V$ ,  $V_{OUT}=1.2V$ ,  $I_{OUT}=4A$




## Transient

$I_{OUT}=2A$  to  $4A$ ,  $2.5A/\mu s$




## VIN Start-Up

$I_{OUT}=0A$









## VIN Start-Up

$I_{OUT}=4A$








# TYPICAL PERFORMANCE CHARACTERISTICS *(continued)*

$V_{IN} = 5V$ ,  $V_{OUT} = 1.2V$ ,  $L = 1\mu H$ ,  $T_A = +25^\circ C$ , unless otherwise noted.



# TYPICAL PERFORMANCE CHARACTERISTICS *(continued)*

$V_{IN} = 5V$ ,  $V_{OUT} = 1.2V$ ,  $L = 1\mu H$ ,  $T_A = +25^\circ C$ , unless otherwise noted.



## PRINTED CIRCUIT BOARD LAYOUT




Figure 1: Top Silk Layer




Figure 2: Top Layer




Figure 3: Inner 1 Layer




Figure 4: Inner 2 Layer




Figure 5: Bottom Layer

## QUICK START GUIDE

1. Connect the positive and negative terminals of the load to the VOUT and GND pins, respectively.
2. Preset the power supply output between 2.7V and 5.5V, and then turn off the power supply.
3. Connect the positive and negative terminals of the power supply output to the VIN and GND pins, respectively.
4. Turn the power supply on. The board will automatically start up.
5. To use the Enable function, apply a digital input to the EN pin. Drive EN higher than 1.2V to turn on the regulator or less than 0.4V to turn it off.

## LAYOUT RECOMMENDATION OF MP2174C

Proper layout of the switching power supplies is very important, and sometimes critical to make it work properly. Especially, for the high switching converter, if the layout is not carefully done, the regulator could show poor line or load regulation, stability issues.

For MP2174C, the high speed step-down regulator, the input capacitor should be placed as close as possible to the IC pins. As shown in Figure 6, the 0805 size ceramic capacitor is used, please make sure the two ends of the ceramic capacitor be directly connected to PIN1 (the Power Input Pin) and PIN 3 (the Power GND Pin).




Figure 6: Two ends of Input decoupling Capacitor close to Pin 1 and Pin 3

**NOTICE:** The information in this document is subject to change without notice. Please contact MPS for current specifications. Users should warrant and guarantee that third party Intellectual Property rights are not infringed upon when integrating MPS products into any application. MPS will not assume any legal responsibility for any said applications.