

AP54RHC420

Radiation-Hardened Dual Quad-SR Latch with cold sparing and Schmitt trigger inputs

1 GENERAL DESCRIPTION

The **AP54RHC420** is a radiation-hardened by design dual quad-SR latch that is ideally suited for commercial space and other applications demanding radiation tolerance and high reliability. It delivers high resiliency to single-event effects (SEE) and to a total ionizing dose (TID).

The AP54RHC420 features Schmitt-triggered inputs. The inputs and/or outputs can be cross-strapped with no impact to operation or leakage current, which simplifies cold-sparing implementation. The redundant output stage has high drive capability with low static power loss.

Ordering information may be found in [Table 10](#) on [Page 15](#).

1.3 FEATURES

- 5 ns transient detection at $V_{CC} > 3\text{ V}$
- SEL/SEFI/SET immune to LET of $75\text{ MeV-cm}^2/\text{mg}$
- 1.4 V to 5.5 V operation
- Schmitt triggers on inputs
- Cold sparing Inputs and Outputs
- Single-supply Level Translation
- TID RLAT 30 krad (Si) at 5.5 V
- Operating temperature range $-55\text{ }^{\circ}\text{C}$ to $+125\text{ }^{\circ}\text{C}$
- Meets NASA's ASTM E595 outgassing specification
- Moisture Sensitivity Level 1 (Unlimited)

1.1 DEVICE INFORMATION

PART NUMBER	GRADE	Package
AP54RHC420ANT ⁽¹⁾	A-Grade Flight (LEO)	TSSOP-20 Plastic mass 74 mg
AP54RHC420BNT ⁽¹⁾	B-Grade Flight (LEO)	
AP54RHC420CNT ⁽¹⁾	C-Grade Flight (LEO)	
AP54RHC420ENT	E-Grade (Evaluation)	

⁽¹⁾ Release in June 2026.

1.2 APPLICATIONS

- System-level glitch latching
- Power supply transient detection
- FDIR: Fault Detection, Isolation, and Recovery
- Single-bit latching
- Discrete state machines
- SEE fault detection in non-rad hard components




Figure 1: AP54RHC420 Logic Diagram

[†] See [detailed note](#).

CONTENTS

1 General Description	1	5.6 Characteristics Measurement Information	9
1.1 Device Information	1	6 Detailed Description	9
1.2 Applications	1	6.1 Overlapping $\bar{S}$ and $\bar{R}$ pulses	10
1.3 Features	1	7 Applications Information	11
2 Acronyms and Abbreviations	2	7.1 Use in Cold-Sparing Configuration	11
3 Logic Data	3	7.2 PMIC Power Good Latching	11
3.1 Truth Table	3	7.3 Power Supply Recommendations	13
4 Pin Configuration	3	7.4 Application Tips	13
5 Electrical Characteristics	4	8 Packaging Information	14
5.1 Absolute Maximum Ratings	4	9 Ordering Information	15
5.2 Recommended Operating Conditions	5	10 Revision History	17
5.3 Static Characteristics	6	11 Legal	18
5.4 Dynamic Characteristics	8		
5.5 Radiation Resilience	9		

LIST OF TABLES

1 Truth Table	3	6 DC Electrical Characteristics	7
2 Device Pinout	4	7 DC Electrical Transfer Characteristics	8
3 Absolute Maximum Ratings	5	8 AC Electrical Characteristics	8
4 Recommended Operating Conditions	5	9 Radiation Resilience Characteristics	9
5 Thermal Information	6	10 Ordering Information	15

LIST OF FIGURES

1 AP54RHC420 Logic Diagram	1	8 Overlapping pulses with long reset	10
2 Device Pinout	3	9 Two-Path Cold-Sparing Configuration	11
3 Load Circuit	9	10 Latched and Unlatched PMIC Fault Detection	12
4 Propagation Delay	9	11 Latched PMIC Fault Detection	12
5 Input Pin Structure	10	12 Package Mechanical Drawing (NiPdAu)	14
6 Output Pin Structure	10	13 Part Number Decoder	16
7 Overlapping pulses with long set	10		

2 ACRONYMS AND ABBREVIATIONS

ESD	Electrostatic Discharge	SET	Single Event Transient
POR	Power On Reset	TID	Total Ionizing Dose
RHA	Radiation Hardness Assurance	TMR	Triple Modular Redundancy
SEE	Single Event Effects	CDM	Charged-device Model
SEL	Single Event Latchup	HBM	Human-body Model

3 LOGIC DATA

3.1 TRUTH TABLE

The AP54RHC420 truth table is found in [Table 1](#). **H** indicates HIGH logic level and **L** indicates LOW logic level.

Table 1: AP54RHC420 Device Truth Table

Input		Output
$\bar{S}$	$\bar{R}$	Q
L	L	H
L	H	H
H	L	L
H	H	No Change

4 PIN CONFIGURATION




Figure 2: AP54RHC420 Device Pinout

Table 2: AP54RHC420 Device Pinout

PIN NAME(S)	PIN NUMBER(S)	DESCRIPTION
1S1	2	Active-Low Set Inputs
1S2	3	
1S3	4	
1S4	5	
2S1	6	
2S2	7	
2S3	8	
2S4	9	
1R	1	Active-Low Reset Inputs
2R	11	
1Q1	19	Outputs
1Q2	18	
1Q3	17	
1Q4	16	
2Q1	15	
2Q2	14	
2Q3	13	
2Q4	12	
V _{CC}	20	Positive Voltage Supply
GND	10	Ground

5 ELECTRICAL CHARACTERISTICS

The sign convention for current follows JEDEC standards with negative values representing current sourced from the device and positive values representing current sunk into the device.

5.1 ABSOLUTE MAXIMUM RATINGS

Excursions beyond the values listed in [Table 3](#) may cause permanent damage to the device. Proper function of the device cannot be guaranteed if these values are exceeded, and long-term device reliability may be affected. Functionality of the device at these values, or beyond those listed in [Recommended Operating Conditions \(Table 4\)](#) is not guaranteed.

All parameters are specified across the entire operating temperature range unless otherwise specified.

Table 3: Absolute Maximum Ratings

SYMBOL	PARAMETER	VALUE	UNITS
V_{CC}	Supply Voltage	-0.5 to +5.5	V
V_I	Input voltage range	-0.5 to +5.5	V
V_O	Output voltage range	-0.5 to +5.5	V
$I_{IK} (V_I < 0)$	Input clamp current	100	mA
I_O	Continuous output current (per pin)	100	mA
I_{CC}	Maximum supply current	100	mA
V_{ESD}	ESD Voltage	HBM 1000	V
		CDM 500	V
T_J	Operating junction temperature range	-55 to +150	°C
T_{STG}	Storage temperature range	-65 to +150	°C

5.2 RECOMMENDED OPERATING CONDITIONS

All parameters are specified across the entire operating temperature range unless otherwise specified. For A-grade flight and B-grade flight parts, all parameters are specified over the entire recommended voltage range of 1.4 V to 5.5 V. For C-grade flight and E-grade Evaluation parts, all parameters are specified over the voltage range of 1.65 V to 5.5 V.

Table 4: Recommended Operating Conditions

SYMBOL	PARAMETER		MIN	TYP	MAX	UNITS
V _{CC}	Supply voltage (A-grade flight, B-grade flight)		1.4	-	5.5	V
V _{CC}	Supply voltage (C-grade flight, E-grade Evaluation)		1.65	-	5.5	V
V _I	Input voltage range		0	-	5.5	V
V _O	Output voltage range		0	-	V _{CC}	V
I _{OH}	HIGH-level output current	V _{CC} = 1.4 to 1.6 V	-	-	-2	mA
		V _{CC} = 1.65 to 1.95 V	-	-	-4	
		V _{CC} = 2.3 to 2.7 V	-	-	-8	
		V _{CC} = 3.0 to 3.6 V	-	-	-16	
		V _{CC} = 4.5 to 5.5 V	-	-	-24	
I _{OL}	LOW-level output current	V _{CC} = 1.4 to 1.6 V	-	-	2	mA
		V _{CC} = 1.65 to 1.95 V	-	-	4	
		V _{CC} = 2.3 to 2.7 V	-	-	8	
		V _{CC} = 3.0 to 3.6 V	-	-	16	
		V _{CC} = 4.5 to 5.5 V	-	-	24	

Table 4: Recommended Operating Conditions continued

SYMBOL	PARAMETER	MIN	TYP	MAX	UNITS
$t_{pw_rst}^{(1)}$	Minimum Pulse Width for Reset	$V_{CC} = 1.4$ to 1.6 V	-	15	19
		$V_{CC} = 1.65$ to 1.95 V	-	11	18
		$V_{CC} = 2.3$ to 2.7 V	-	7	16
		$V_{CC} = 3.0$ to 3.6 V	-	5	14
		$V_{CC} = 4.5$ to 5.5 V	-	4.5	9
$t_{pw_set}^{(1)}$	Minimum Pulse Width for Set	$V_{CC} = 1.4$ to 1.6 V	-	14	24
		$V_{CC} = 1.65$ to 1.95 V	-	9.5	23
		$V_{CC} = 2.3$ to 2.7 V	-	6	20
		$V_{CC} = 3.0$ to 3.6 V	-	4.5	17
		$V_{CC} = 4.5$ to 5.5 V	-	4.3	11
$t_{d_rst}^{(1) (2)}$	Delay after set for reset to avoid ambiguity for overlapping pulses	$V_{CC} = 1.4$ to 1.6 V	5.0	-	-
		$V_{CC} = 1.65$ to 1.95 V	4.7	-	-
		$V_{CC} = 2.3$ to 2.7 V	4.1	-	-
		$V_{CC} = 3.0$ to 3.6 V	3.4	-	-
		$V_{CC} = 4.5$ to 5.5 V	2.0	-	-
$t_{d_set}^{(1) (3)}$	Delay after reset for set to avoid ambiguity for overlapping pulses	$V_{CC} = 1.4$ to 1.6 V	7.9	-	-
		$V_{CC} = 1.65$ to 1.95 V	7.5	-	-
		$V_{CC} = 2.3$ to 2.7 V	6.4	-	-
		$V_{CC} = 3.0$ to 3.6 V	5.2	-	-
		$V_{CC} = 4.5$ to 5.5 V	2.7	-	-

(1) guaranteed by design

(2) For t_{d_rst} , refer to [Figure 7 \(Detailed Description\)](#).(3) For t_{d_set} , refer to [Figure 8 \(Detailed Description\)](#).

Table 5: Thermal Information

SYMBOL	PARAMETER	MIN	TYP	MAX	UNITS
T_J	Operating junction temperature	-55	-	+125	°C
$R_{\theta JA}$	Junction to ambient thermal resistance	-	100	-	°C/W

5.3 STATIC CHARACTERISTICS

All parameters are specified across the entire operating temperature range unless otherwise specified. For A-grade flight and B-grade flight parts, all parameters are specified over the entire recommended voltage range of 1.4 V to 5.5 V. For C-grade flight and E-grade Evaluation parts, all parameters are specified over the voltage range of 1.65 V to 5.5 V.

Table 6: DC Electrical Characteristics

SYMBOL	PARAMETER	CONDITIONS	V _{CC}	MIN	TYP	MAX	UNITS
V _{OL}	LOW-Level Output Voltage	I _O = 100 µA	1.4 to 5.5 V	-	0.02	0.05	V
		I _O = 1 mA	1.4 to 5.5 V	-	0.05	0.15	V
		I _O = 4 mA	1.65 V	-	0.27	0.8	V
			2.3 V	-	0.3	0.6	V
			3.0 V	-	0.2	0.4	V
			4.5 V	-	0.2	0.4	V
		I _O = 8 mA	2.3 V	-	0.6	1.0	V
			3.0 V	-	0.4	0.8	V
			4.5 V	-	0.3	0.6	V
		I _O = 16 mA	3.0 V	-	1.0	1.4	V
			4.5 V	-	1.1	1.2	V
		I _O = 24 mA	4.5 V	-	1.1	1.5	V
V _{OH}	HIGH-Level Output Voltage	I _O = -100 µA	1.4 to 5.5 V	V _{CC} - 0.1	V _{CC} - 0.02	-	V
		I _O = -1 mA	1.4 to 5.5 V	V _{CC} - 0.15	V _{CC} - 0.08	-	V
		I _O = -4 mA	1.65 V	1	1.35	-	V
			2.3 V	1.8	2.0	-	V
			3.0 V	2.6	2.8	-	V
			4.5 V	4.2	4.4	-	V
		I _O = -8 mA	2.3 V	1.4	1.7	-	V
			3.0 V	2.2	2.5	-	V
			4.5 V	3.9	4.1	-	V
		I _O = -16 mA	3.0 V	1.5	2.0	-	V
			4.5 V	3.3	3.8	-	V
		I _O = -24 mA	4.5 V	3.0	3.5	-	V
I _{CC}	Quiescent supply current	V _I = V _{CC} or GND I _O = 0 mA	1.6 V	-	43	75	µA
			1.95 V	-	48	85	µA
			3.6 V	-	125	195	µA
			5.5 V	-	247	400	µA
		V _I = V _{CC} or GND I _O = 0 mA T _a = 25°C, Post TID	5.5 V	-	527	564	µA
I _I	Input current	V _I = V _{CC} or GND	1.4 to 5.5 V	-1	-	1	µA
I _{OFF}	Powerdown leakage current ⁽¹⁾	V _I = V _{CC} or GND	OFF ⁽²⁾	-	-	5	µA

⁽¹⁾ into any input or output port⁽²⁾ V_{CC} is at GND potential

Table 7: DC Electrical Transfer Characteristics

SYMBOL	PARAMETER	V _{CC}	MIN	TYP	MAX	UNITS
$V_{T+}^{(1)}$	Positive-going threshold voltage	1.40 V	0.80	0.99	1.10	V
		1.65 V	0.99	1.12	1.21	V
		2.30 V	1.35	1.54	1.65	V
		3.00 V	1.72	1.97	2.10	V
		4.50 V	2.60	2.88	3.06	V
		5.50 V	3.01	3.48	3.68	V
V_{T-}	Negative-going threshold voltage	1.40 V	0.45	0.55	0.60	V
		1.65 V	0.53	0.62	0.80	V
		2.30 V	0.76	0.87	1.10	V
		3.00 V	1.00	1.16	1.45	V
		4.50 V	1.53	1.79	2.10	V
		5.50 V	1.95	2.22	2.50	V
$\Delta V_T^{(1)}$	Input hysteresis ($V_{T+} - V_{T-}$)	1.40 V	0.20	0.44	0.60	V
		1.65 V	0.32	0.50	0.62	V
		2.30 V	0.45	0.67	0.80	V
		3.00 V	0.60	0.82	1.00	V
		4.50 V	0.80	1.10	1.25	V
		5.50 V	0.95	1.26	1.42	V

⁽¹⁾ Tested on Set, guaranteed by similarity on Reset.

5.4 DYNAMIC CHARACTERISTICS

All parameters are specified across the entire operating temperature range unless otherwise specified. For A-grade flight and B-grade flight parts, all parameters are specified over the entire recommended voltage range of 1.4 V to 5.5 V. For C-grade flight and E-grade Evaluation parts, all parameters are specified over 1.65 V to 5.5 V.

Table 8: AC Electrical Characteristics

SYMBOL	PARAMETER	CONDITIONS	V _{CC}	MIN	TYP	MAX	UNITS
$t_{pd}^{(1)}$	Propagation Delay (Falling edge $\bar{S}_n$ to output Q)	$C_L = 50$ pF	4.5 to 5.5 V	-	12	16	ns
			3.0 to 3.6 V	-	20	28	ns
			2.3 to 2.7 V	-	24	34	ns
			1.65 to 1.95 V	-	27	39	ns
			1.4 to 1.6 V	-	28	41	ns
$t_{pd}^{(1)}$	Propagation Delay (Falling edge $\bar{R}_n$ to output Q)	$C_L = 50$ pF	4.5 to 5.5 V	-	10	14	ns
			3.0 to 3.6 V	-	16	25	ns
			2.3 to 2.7 V	-	19	29	ns
			1.65 to 1.95 V	-	22	34	ns
			1.4 to 1.6 V	-	23	35	ns
C_{in}	Input Capacitance ⁽¹⁾	$V_I = V_{CC}$ or GND	1.4 to 5.5 V	-	2	4	pF
C_{pd}	Power Dissipation Capacitance ⁽¹⁾	$I_O = 0$ mA $f = 1$ MHz	5.5 V	-	40	-	pF

⁽¹⁾ guaranteed by design

5.5 RADIATION RESILIENCE

For detailed radiation testing reports, please contact Apogee Semiconductor at sales@apogeesemi.com.

Table 9: Radiation Resilience Characteristics

PARAMETER	CONDITIONS	VALUE	UNITS
Total Ionizing Dose (TID)	Please contact Apogee Semiconductor for test report.	30	krad (Si)
SEL Onset LET Threshold	Please contact Apogee Semiconductor for test report.	≥ 75	MeV-cm ² /mg

5.6 CHARACTERISTICS MEASUREMENT INFORMATION




Figure 3: Load Circuit




Figure 4: Propagation Delay Measurement

6 DETAILED DESCRIPTION

The AP54RHC420 is an dual quad-SR latch intended to latch short duration active low transient events. Designed to operate from a wide supply voltage of 1.4 to 5.5 V, it has fully redundant input and output stages and internal states providing for superior resiliency to single event effects, including single event upsets (SEU).

The eight SR latches are implemented as two units, each containing four individual active low set inputs, one common active low reset input and four separate outputs. The set inputs are dominant, which means that if set and reset are both active at the same time, set will prevail over reset.

Note that if the Power On Reset is active, the outputs will be tristate. On leaving POR, if both SET and RESET inputs are high, i.e. inactive, the state of the SR latches will initially be indeterminate, i.e. the Q outputs could be high or low.

A typical application for this part might be to monitor "power good" signals from PMICs, LDOs or other devices: if one of these signals transitions low for a short period, these latches can capture that event and present it for detection at the inputs of an Apogee Semiconductor API016 GPIO expander, which can in turn alert the control system that a transient event has been detected.

The output and input stages are constructed with transient-activated clamps (Figure 5, Figure 6) that prevent inadvertent biasing of the V_{CC} power rail through parasitic diodes inherent to conventional input, output, and ESD circuits. The IC also incorporates an internal power-on reset (POR) circuit that prevents the output from driving erroneous results during power-on, and guarantees correct operation at power supply voltages as low as 1.4 V. While the supply is ramping, the POR holds the output buffers in tri-state, a feature that prevents unwanted DC current during cold sparing on input and output pins.

The AP54RHC family's I/O protection circuitry allows for cold sparing configurations as it avoids a leakage current penalty on inputs and outputs while in a power-down state. This can result in considerable power savings in

systems where multiple-path redundancy is employed. The ESD clamp circuits for this logic family are designed to support Class 1C ESD levels of 1 kV HBM and 500 V CDM.




Figure 5: Input Pin Structure




Figure 6: Output Pin Structure

6.1 OVERLAPPING $\bar{S}$ AND $\bar{R}$ PULSES

When the active-low pulses on $\bar{S}$ and $\bar{R}$ overlap, a minimum separation between their de-asserting (rising) edges is required so that the latch does not resolve to an indeterminate output state. If $\bar{S}$ de-asserts first, $\bar{R}$ must remain low for at least t_{d_rst} after $\bar{S}$ rises (Figure 7). If $\bar{R}$ de-asserts first, $\bar{S}$ must remain low for at least t_{d_set} after $\bar{R}$ rises (Figure 8).




Figure 7: Overlapping pulses with long set




Figure 8: Overlapping pulses with long reset

7 APPLICATIONS INFORMATION

The Schmitt trigger operation of this gate allows for it to be used in applications where input signals with slow ramps or additive noise exist. Slow rising input signals into CMOS inputs may cause “shoot-through” to occur on conventional input gates, but is resolved by the Schmitt trigger operation of the AP54RHC420 and its input hysteresis that results in no input rise or fall time limitations. Additionally, the Schmitt trigger operation and level conversion offered by this IC will guarantee that gate outputs exhibit clean and fast transitions at the appropriate V_{CC} level(s).

7.1 USE IN COLD-SPARING CONFIGURATION

As the AP54RHC family is radiation-hardened by design and includes internal TMR, it can be utilized in high-reliability applications without additional supporting circuitry or devices. Nonetheless, some application requirements call for fully-redundant designs, where an “A” and a “B” device are required, often on separate power rails.




Figure 9: Two-Path Cold-Sparing Configuration

With the cold sparing capability of the AP54RHC family, fully redundant “A” and “B” functions may be placed in parallel (as seen in [Figure 9](#)) running off redundant power supplies. The inputs and outputs on each one of these functions are assumed to be based on the AP54RHC family, allowing for direct parallel connection without unwanted leakage current paths during cold sparing. In the event of a failure in power supply A or within function A, the system can simply shut power supply A off and switch on power supply B, without requiring additional input or output switching or configuration changes.

7.2 PMIC POWER GOOD LATCHING

A typical application for this part might be to monitor “power good” signals from PMICs, LDOs or other devices: if one of these signals transitions low for a short period, these latches can capture that event and present it for detection at the inputs of an Apogee Semiconductor [APIO16](#) GPIO expander, which can in turn alert the control system that a transient event has been detected.

AP54RHC420

DATASHEET

Rad-Hard Dual Quad-SR Latch

with cold sparing and Schmitt trigger inputs



**Figure 10:** Latched and Unlatched PMIC Fault Detection

Figure 10 shows the AP54RHC420 used to latch the power good (PG) signals from five separate PMICs. As with the application described above, the device can capture any low transients on the PG signals so that transient faults are not missed. The diagram illustrates the AP54RHC420 interfacing with an APIO16 I/O expander, which enables the controller (OBC in the diagram) to detect faults on multiple PMICs without consuming many I/Os. The change of state of the APIO16 can trigger an interrupt to the OBC to initiate reading the APIO16.

Also shown in Figure 10 is the PG signals from the PMICs connected directly to the APIO16 through the bottom-most trace. This enables the APIO16 to monitor both the latched signals and the current value of the PG signals, so that it can diagnose both a fault and the current state of the PMICs. In the event this level of monitoring is not needed a single AP54RHC420 can be used to latch the PG signals of up to eight PMICs as shown in Figure 11.

**Figure 11:** Latched PMIC Fault Detection

Some systems may desire to capture transients that do not fully drive an open-drain network below the standard V_{IL} threshold at that voltage node. A solution may exist by operating the AP54RHC420 at a higher V_{CC} than the PMIC in order to scale the minimum V_{T-} to a higher value. Additionally, adjusting the pull-up rail voltage on the open-drain network must ensure that the voltage seen when the signal is high impedance is above the V_{T+} threshold.

7.3 POWER SUPPLY RECOMMENDATIONS

This device can operate at any voltage within the range specified in [Table 4 Recommended Operating Conditions](#).

At a minimum, a 16 VDC (or higher), X7R-rated 0.1 μ F ceramic decoupling capacitor should be placed near (within 1 cm) the V_{CC} pin of the device.

7.4 APPLICATION TIPS

Unused **inputs** must **not** be left floating. They may be connected to either a low (GND) or high (V_{CC}) bias to provide a known state at the input of the device. Resistors may be used to tie off unused inputs. In the event of a design change, such resistors can be removed, thereby allowing use of the inputs without having to cut traces on the PCB.


An unused **output** may be left floating. It is suggested that it be routed to a test point or similar accessible structure in case the gate needs to be utilized as part of a design revision.

AP54RHC420

DATASHEET

Rad-Hard Dual Quad-SR Latch

with cold sparing and Schmitt trigger inputs

8 PACKAGING INFORMATION**Notes:**

1. All linear dimensions are in millimeters. Dimensioning and tolerancing are as per ISO/TS 128-71:2010
2. The part is compliant with JEDEC MO-153 specifications.

* Body width does **not** include interlead flash. Interlead flash shall not exceed 0.25 mm each side.

** Body length does **not** include mold flash, protrusion, or gate burrs. Mold flash, protrusions, and gate burrs shall not exceed 0.15 mm on each side.

Figure 12: 20-NT - Package Mechanical Drawing (NiPdAu)

9 ORDERING INFORMATION

Example part numbers for the AP54RHC420 are listed in [Table 10](#). The full list of options for this part can be found in [Figure 13](#). For a detailed description of product grades, please refer to [Product Grades and Quality Flows document](#). Please contact Apogee Semiconductor sales at sales@apogeesemi.com for further information on sampling, lead time and purchasing on specific part numbers.

Table 10: AP54RHC420 Ordering Information


DEVICE	DESCRIPTION	PACK-AGING	PACKAGE	LEAD FINISH	STATUS
AP54RHC420ANT-R	Rad-Hard Dual Quad-SR Latch (A-Grade Flight)	Reel	TSSOP-20	NiPdAu	Plan Rls JUN-2026
AP54RHC420BNT-R	Rad-Hard Dual Quad-SR Latch (B-Grade Flight)	Reel	TSSOP-20	NiPdAu	Plan Rls JUN-2026
AP54RHC420CNT-R	Rad-Hard Dual Quad-SR Latch (C-Grade Flight)	Reel	TSSOP-20	NiPdAu	Plan Rls JUN-2026
AP54RHC420ENT-R	Rad-Hard Dual Quad-SR Latch (E-Grade for Evaluation)	Reel	TSSOP-20	NiPdAu	Available

AP54RHC420

DATASHEET

Rad-Hard Dual Quad-SR Latch

with cold sparing and Schmitt trigger inputs

**Figure 13:** Part Number Decoder

1. RHA Designation
 - P** 30 krad (Si)
 - F** 300 krad (Si)
2. Part Number
 - 420** (Dual Quad-SR Latch)
3. Pedigree
 - A** -55 to +125 °C (Burn-in)
 - B** -55 to +125 °C (No burn-in)
 - C** 25 °C (No burn-in)
 - E** 25 °C Functional Test Only (Evaluation)
4. Lead Finish
 - N** Nickel-Palladium-Gold (NiPdAu)
5. Package
 - T** 20-pin Thin Shrink Small Outline Package (TSSOP-20)
6. Packaging
 - R** Tape and Reel⁽¹⁾

⁽¹⁾ [Contact us](#) for custom reel quantities. Orders less than full reel quantities may be shipped as cut tape.

10 REVISION HISTORY

REVISION	DESCRIPTION	DATE
B00	Initial Release.	2026-May-06

For the latest version of this document, please visit <https://www.apogeesemi.com>.

11 LEGAL

All product, product specifications and data are subject to change without notice.

Apogee Semiconductor provides technical data (such as datasheets), design resources (including reference designs), reliability data (including performance in radiation environments), application or other design advice, safety information, and other resources “as is” and with all faults, and disclaims all warranties, express and implied, including without limitation any implied warranties of merchantability, fitness for a particular purpose or non-infringement of third party intellectual property rights. These resources are intended for skilled engineers with understanding of high reliability and high radiation environments and its complexities.

Apogee Semiconductor is not responsible for: (1) selecting the suitable products for a given application, (2) designing, verifying, validating and testing it, or (3) ensuring that it meets any performance, safety, security, or other requirements. These resources are subject to change without advance notice. The use of these resources is restricted to the development of an application that uses the Apogee Semiconductor products described in them. Other reproduction and display of these resources is prohibited. No license is granted to any other Apogee Semiconductor intellectual property right or to any third-party intellectual property right.

Apogee Semiconductor disclaims responsibility and reserves the right to demand indemnification for any claims, damages, costs, losses, and liabilities arising out of wrongful use of these resources. The products are provided subject to Apogee Semiconductor's [Terms of Sale](https://www.apogeesemi.com/terms) (<https://www.apogeesemi.com/terms>) or other applicable terms provided in conjunction with applicable products. The provision of these resources does not expand or otherwise alter applicable warranties or warranty disclaimers for Apogee Semiconductor products.

Purchasers of these products acknowledge that they may be subject to and agree to abide by the United States laws and regulations controlling the export of technical data, computer software, electronic hardware and other commodities. The transfer of such items may require a license from the cognizant agency of the U.S. Government.

[†] DATASHEET RELEASE STATUS DEFINITIONS

This datasheet is labeled with its status on the cover and at the top of each page to indicate specification maturity and the likelihood of change. The definitions below explain what each label means:

1. **Preliminary** — Created during product design and early development. Provides initial specifications, anticipated performance metrics, and other critical data used to gather targeted customer feedback. Specifications are based on design intent and simulation and may include limited early lab data. Specifications are subject to change, and TBD values may be present.
2. **Pre-production** — Status at the time of E grade release to market. Specifications are supported by simulation and initial device characterization, with few to no TBDs. Limits are not yet finalized and may change prior to Production release.
3. **Production** — Status at the time of flight grade release to market. Final, controlled datasheet with confirmed specifications, performance metrics, and compliance information verified through qualification and production test. Any future specification updates will follow the formal PCN process.