

ESP32-P4

esp-dev-kits Documentation



Release master
Espressif Systems
May 22, 2026

Table of contents

Table of contents	i
1 ESP32-P4X-Function-EV-Board	3
1.1 ESP32-P4X-Function-EV-Board	3
1.1.1 Getting Started	5
1.1.2 Hardware Reference	13
1.1.3 Hardware Revision Details	15
1.1.4 Related Documents	15
2 ESP32-P4X-EYE	17
2.1 ESP32-P4X-EYE	17
2.1.1 Getting Started	17
2.1.2 Hardware Reference	24
2.1.3 Hardware Revision Details	26
2.1.4 Related Documents	26
3 EOL (End of Life) Boards	31
3.1 ESP32-P4-Function-EV-Board	31
3.1.1 ESP32-P4-Function-EV-Board v1.5.2	31
3.2 ESP32-P4-EYE	48
3.2.1 ESP32-P4-EYE	48
4 Related Documentation and Resources	63
4.1 Developer Zone	63
4.2 Products	63
4.3 Contact Us	63
5 Disclaimer and Copyright Notice	65

This document provides detailed user guides and examples for ESP32-P4 series development boards.

Note: For the full list of Espressif development boards, please go to [ESP DevKits](#).

Chapter 1

ESP32-P4X-Function-EV-Board

ESP32-P4X-Function-EV-Board is a multimedia development board based on the ESP32-P4 chip. ESP32-P4 chip features a dual-core RISC-V processor and supports up to 32 MB PSRAM. In addition, ESP32-P4 supports USB 2.0 specification, MIPI-CSI/DSI, H264 Encoder, and various other peripherals. With all of its outstanding features, the board is an ideal choice for developing low-cost, high-performance, low-power network-connected audio and video products.

1.1 ESP32-P4X-Function-EV-Board

Note: The ESP32-P4X-Function-EV-Board with the ESP32-P4 chip revision v3.1 does not support Secure Download. Please do not enable Secure Download Mode. For more details, please refer to [ESP32-P4 Series SoC Errata > ROM-770](#).

To identify the embedded chip revision, refer to [ESP32-P4 Series SoC Errata > Chip Revision Identification](#).

This user guide will help you get started with ESP32-P4X-Function-EV-Board and will also provide more in-depth information.

ESP32-P4X-Function-EV-Board is a multimedia development board based on the ESP32-P4 chip. ESP32-P4 chip features a dual-core RISC-V processor and supports up to 32 MB PSRAM. In addition, ESP32-P4 supports USB 2.0 specification, MIPI-CSI/DSI, H264 Encoder, and various other peripherals. With all of its outstanding features, the board is an ideal choice for developing low-cost, high-performance, low-power network-connected audio and video products.

The 2.4 GHz Wi-Fi 6 & Bluetooth 5 (LE) module ESP32-C6-MINI-1 serves as the Wi-Fi and Bluetooth module of the board. The board also includes a 7-inch capacitive touch screen with a resolution of 1024 x 600 and a 2MP camera with MIPI CSI, enriching the user interaction experience. The development board is suitable for prototyping a wide range of products, including visual doorbells, network cameras, smart home central control screens, LCD electronic price tags, two-wheel vehicle dashboards, etc.

Most of the I/O pins are broken out to the pin headers for easy interfacing. Developers can connect peripherals with jumper wires.

The document consists of the following major sections:

- [Getting Started](#): Overview of ESP32-P4X-Function-EV-Board and hardware/software setup instructions to get started.
- [Hardware Reference](#): More detailed information about the ESP32-P4X-Function-EV-Board's hardware.
- [Hardware Revision Details](#): Revision history, known issues, and links to user guides for previous versions (if any) of ESP32-P4X-Function-EV-Board.




Fig. 1: ESP32-P4X-Function-EV-Board

- [Related Documents](#): Links to related documentation.

1.1.1 Getting Started

This section provides a brief introduction to ESP32-P4X-Function-EV-Board, instructions on how to do the initial hardware setup and how to flash firmware onto it.

Description of Components




Fig. 2: ESP32-P4X-Function-EV-Board - front (click to enlarge)

The key components of the board are described from front view to back view, starting from the J1, in a clockwise direction.




Fig. 3: ESP32-P4X-Function-EV-Board - back (click to enlarge)

No.	Key Component	Description
1	J1	All available GPIO pins are broken out to the header block J1 for easy interfacing. For more details, see Header Block .
2	ESP32-C6 Module Programming Connector	The connector can be used with ESP-Prog or other UART tools to flash firmware onto the ESP32-C6 module.
3	ESP32-C6-MINI-1 Module	This module serves as the Wi-Fi and Bluetooth communication module for the board.
4	Microphone	Onboard microphone connected to the interface of Audio Codec Chip.
5	Reset Button	Resets the board.
6	Audio Codec Chip	ES8311 is a low-power mono audio codec chip. It includes a single-channel ADC, a single-channel DAC, a low-noise pre-amplifier, a headphone driver, digital sound effects, analog mixing, and gain functions. It interfaces with the ESP32-P4 chip over I2S and I2C buses to provide hardware audio processing independent of the audio application.
7	Speaker Output Port	This port is used to connect a speaker. The maximum output power can drive a 4 Ω , 3 W speaker. The pin spacing is 2.00 mm (0.08").
8	Audio PA Chip	NS4150B is an EMI-compliant, 3 W mono Class D audio power amplifier that amplifies audio signals from the audio codec chip to drive speakers.
9	5 V to 3.3 V LDO	A power regulator that converts a 5 V supply to a 3.3 V output.
10	BOOT Button	The boot mode control button. Press the Reset Button while holding down the Boot Button to reset ESP32-P4 and enter firmware download mode. Firmware can then be downloaded to SPI flash via the USB Serial/JTAG Port.
11	Ethernet PHY IC	Ethernet PHY chip connected to the ESP32-P4 EMAC RMII interface and RJ45 Ethernet Port.
12	Buck Converter	A buck DC-DC converter for the 3.3 V power supply.
13	5 V Power-on LED	This LED lights up when the board is powered through any USB Type-C port.
14	RJ45 Ethernet Port	An Ethernet Port supporting 10/100 Mbps adaptive.

No.	Key Component			Description
15	USB Port	Full-speed		USB Type-C port that supports USB 2.0 Full-speed data rate. It can be used as the power supply interface for the development board and as a communication interface.
16	USB Port	Serial/JTAG		USB Type-C port that supports USB 2.0 Full-speed data rate. It can be used to flash firmware to the ESP32-P4 chip, communicate with the chip via the USB protocol, and perform JTAG debugging.
17	USB Port	2.0 Type-C		The USB 2.0 Type-C Port is connected to the USB 2.0 OTG High-Speed interface of ESP32-P4, compliant with the USB 2.0 specification. When communicating with other devices via this port, ESP32-P4 acts as a USB device connecting to a USB host. Please note that USB 2.0 Type-C Port and USB 2.0 Type-A Port cannot be used simultaneously. USB 2.0 Type-C Port can also be used for powering the board.
18	USB Port	2.0 Type-A		The USB 2.0 Type-A Port is connected to the USB 2.0 OTG High-Speed interface of ESP32-P4, compliant with the USB 2.0 specification. When communicating with other devices via this port, ESP32-P4 acts as a USB host, providing up to 500 mA of current. Please note that USB 2.0 Type-C Port and USB 2.0 Type-A Port cannot be used simultaneously.
19	Power Switch			Power On/Off Switch. Toggling toward the ON sign powers the board on (5 V), toggling away from the ON sign powers the board off.
20	Switch			TPS2051C is a USB power switch that provides a 500 mA output current limit.
21	MIPI CSI Connector			The FPC connector 1.0K-GT-15PB is used for connecting external camera modules to enable image transmission. For details, please refer to 1.0K-GT-15PB specification in Related Documents. FPC specifications: 1.0 mm pitch, 0.7 mm pin width, 0.3 mm thickness, 15 pins.
22	Buck Converter			A buck DC-DC converter for VDD_HP power supply of ESP32-P4.
23	ESP32-P4			A high-performance MCU with large internal memory and powerful image and voice processing capabilities.
24	40 MHz XTAL			An external precision 40 MHz crystal oscillator that serves as a clock for the system.
25	32.768 kHz XTAL			An external precision 32.768 kHz crystal oscillator that serves as a low-power clock while the chip is in deep-sleep mode.
26	MIPI DSI Connector			The FPC connector 1.0K-GT-15PB is used for connecting displays. For details, please refer to 1.0K-GT-15PB Specification in Related Documents. FPC specifications: 1.0 mm pitch, 0.7 mm pin width, 0.3 mm thickness, 15 pins.
27	SPI flash			The 16 MB flash is connected to the chip via the SPI interface.
28	MicroSD Card Slot			The development board supports a MicroSD card in 4-bit mode and can store or play audio files from the MicroSD card.

Note: Usage notes for LDO_VO3 / LDO_VO4:

On the ESP32-P4X-Function-EV-Board, LDO_VO3 and LDO_VO4 are used to power certain on-board VDD domains. Users must configure the correct output voltage and enable state in software.

In Light-sleep or Deep-sleep mode, if LDO_VO3 / LDO_VO4 remain enabled, the system power consumption will be relatively high. Even when turned off, the total power consumption may still exceed the typical low-power specifications listed in the chip datasheet due to the board-level power architecture.

For applications with strict power consumption requirements, it is recommended to optimize the power architecture in custom hardware designs.

Accessories

Optionally, the following accessories are included in the package:

- LCD and its accessories (optional)
 - 7-inch capacitive touch screen with a resolution of 1024 x 600
 - LCD adapter board
 - Accessories bag, including DuPont wires, ribbon cable for LCD, long brass standoffs (20 mm in length), and short brass standoffs (8 mm in length)
- Camera and its accessories (optional)
 - 2MP camera with MIPI CSI
 - Camera adapter board
 - Ribbon cable for camera




Fig. 4: Ribbon Cables in Forward and Reverse Directions

Note: Please note that the ribbon cable in the **forward direction**, whose strips at the two ends are on the same side, should be used for the **camera**; the ribbon cable in the **reverse direction**, whose strips at the two ends are on different sides, should be used for the **LCD**.

Application Examples

The following application examples are available for ESP32-P4X-Function-EV-Board:

- [ESP_Brookesia Phone](#) - Demonstrates an Android-like interface with multiple applications using ESP_Brookesia, utilizing MIPI-DSI, MIPI-CSI, ESP32-C6, SD card, and audio interfaces on a development board, providing a basis for efficient multimedia application development.
- [LVGL Demo v8](#) - Demonstrates how to port LVGL v8 and conduct performance testing using LVGL's built-in demos on an ESP32-P4X-Function-EV-Board with a 7-inch LCD screen, serving as a foundation for developing applications based on LVGL v8.
- [LVGL Demo v9](#) - Demonstrates how to port LVGL v9 and conduct performance testing using LVGL's built-in demos on an ESP32-P4X-Function-EV-Board, serving as a basis for developing applications based on LVGL v9.

For more examples and the latest updates, please refer to the [examples](#) folder.

Alternatively, you can try the factory demo and other prebuilt examples directly in your web browser using [ESP Launchpad](#). ESP Launchpad provides a convenient way to flash firmware to your board without installing ESP-IDF or compiling the source code.

To explore the application examples or to develop your own, please follow the steps outlined in the [Start Application Development](#) section.

Start Application Development

Before powering up your ESP32-P4X-Function-EV-Board, please make sure that it is in good condition with no obvious signs of damage.

Required Hardware

- ESP32-P4X-Function-EV-Board
- USB cables
- Computer running Windows, Linux, or macOS

Note: Be sure to use a good quality USB cable. Some cables are for charging only and do not provide the needed data lines nor work for programming the boards.

Optional Hardware

- MicroSD card

Hardware Setup Connect the ESP32-P4X-Function-EV-Board to your computer using a USB cable. The board can be powered through any of the USB Type-C ports. The USB Serial/JTAG Port is recommended for flashing firmware and debugging.

The figure below shows the overall appearance of the development board, LCD adapter board, and camera once fully assembled. The components description is available in [Components Description of Fully Assembled ESP32-P4X-Function-EV-Board](#).

To connect the LCD, follow these steps:

1. Secure the development board to the LCD adapter board by attaching the short brass standoffs (8 mm in length) to the four standoff posts at the center of the LCD adapter board.
2. Connect the J3 header of the LCD adapter board to the MIPI DSI connector on the ESP32-P4X-Function-EV-Board using the LCD ribbon cable (**reverse direction**). Note that the LCD adapter board is already connected to the LCD.
3. Use a DuPont wire to connect the GPIO27 pin of the J1 header on the ESP32-P4X-Function-EV-Board to the RST_LCD pin of the J6 header on the LCD adapter board. The GPIO mapped to RST_LCD can be configured via software, with GPIO27 set as the default.
4. Use a DuPont wire to connect the GPIO26 pin of the J1 header on the ESP32-P4X-Function-EV-Board to the PWM pin of the J6 header on the LCD adapter board. The GPIO mapped to PWM can be configured via software, with GPIO26 set as the default.
5. It is recommended to power the LCD by connecting a USB cable to the J1 header of the LCD adapter board. If this is not feasible, use DuPont wires to connect the 5V and GND pins of the J1 header on the ESP32-P4X-Function-EV-Board to the 5V and GND pins of the LCD adapter board, provided that the development board has sufficient power supply.

In summary, the ESP32-P4X-Function-EV-Board and the LCD adapter board are connected via the following pins:




Fig. 5: Fully assembled ESP32-P4X-Function-EV-Board




Fig. 6: LCD ribbon cable details




Fig. 7: DuPont wire connections

Table 1: DuPont Wire Connections

ESP32-P4X-Function-EV-Board	LCD Adapter Board
MIPI DSI connector	J3 header
GPIO27 pin of J1 header	RST_LCD pin of J6 header
GPIO26 pin of J1 header	PWM pin of J6 header
5V pin of J1 header	5V pin of J6 header
GND pin of J1 header	GND pin of J6 header

- Attach the long brass standoffs (20 mm in length) to the four standoff posts on the periphery of the LCD adapter board to allow the LCD to stand upright.

Note:

- If you power the LCD adapter board by connecting a USB cable to its J1 header, you do not need to connect its 5V and GND pins to the corresponding pins on the development board.
- To use the camera, connect the camera adapter board to the MIPI CSI connector on the development board using the camera ribbon cable (**forward direction**).

Camera Front (10)




Fig. 8: Camera

Table 2: Components Description of Fully Assembled ESP32-P4X-Function-EV-Board

Component Number	Main Component
1	Long Brass Standoff
2	Camera Ribbon Cable
3	Short Brass Standoff
4	USB Cable
5	LCD Ribbon Cable
6	GPIO27 to RST_LCD
7	GPIO26 to PWM
8	GND to GND
9	5V to 5V
10	Camera Front

Software Setup To set up your development environment and flash an application example onto your board, please follow the instructions in [ESP-IDF Get Started](#).

1.1.2 Hardware Reference

Block Diagram

The block diagram below shows the components of ESP32-P4X-Function-EV-Board and their interconnections.




Fig. 9: ESP32-P4X-Function-EV-Board Block Diagram (click to enlarge)

Power Supply Options

Power can be supplied through any of the following ports:

- USB 2.0 Type-C Port
- USB Full-speed Port
- USB Serial/JTAG Port

If the USB cable used for debugging cannot provide enough current, you can connect the board to a power adapter via any available USB Type-C port.

Header Block

The tables below provide the **Name** and **Function** of the pin header J1 of the board. The pin header names are shown in Figure [ESP32-P4X-Function-EV-Board - front \(click to enlarge\)](#). The numbering is the same as in the schematic of [ESP32-P4X-Function-EV-Board Reference Design](#).

No.	Name	Type ^{Page 15, 1}	Function
1	3V3	P	3.3 V power supply
2	5V	P	5 V power supply
3	7	I/O/T	GPIO7
4	5V	P	5 V power supply
5	8	I/O/T	GPIO8
6	GND	GND	Ground
7	23	I/O/T	GPIO23
8	37	I/O/T	U0TXD, GPIO37
9	GND	GND	Ground
10	38	I/O/T	U0RXD, GPIO38
11	21	I/O/T	GPIO21
12	22	I/O/T	GPIO22
13	20	I/O/T	GPIO20
14	GND	GND	Ground
15	6	I/O/T	GPIO6
16	5	I/O/T	GPIO5
17	3V3	P	3.3 V power supply
18	4	I/O/T	GPIO4
19	3	I/O/T	GPIO3
20	GND	GND	Ground
21	2	I/O/T	GPIO2
22	NC(1)	I/O/T	GPIO1 ²
23	NC(0)	I/O/T	GPIO0 ²
24	36	I/O/T	GPIO36
25	GND	GND	Ground
26	32	I/O/T	GPIO32
27	NC	—	No connection
28	NC	—	No connection
29	33	I/O/T	GPIO33
30	GND	GND	Ground
31	26	I/O/T	GPIO26
32	54	I/O/T	GPIO54
33	48	I/O/T	GPIO48
34	GND	GND	Ground
35	53	I/O/T	GPIO53
36	46	I/O/T	GPIO46
37	47	I/O/T	GPIO47

continues on next page

Table 3 – continued from previous page

No.	Name	Type ^{Page 15, 1}	Function
38	27	I/O/T	GPIO27
39	GND	GND	Ground
40	NC(45)	I/O/T	GPIO45 ³

J1

1.1.3 Hardware Revision Details

The difference between the ESP32-P4X-Function-EV-Board and the *ESP32-P4-Function-EV-Board* is that the main chip on the former has been upgraded to the ESP32-P4 chip revision v3.1 or later version.

1.1.4 Related Documents

Please download the following documents from [the HTML version of esp-dev-kits Documentation](#).

- [ESP32-P4X-Function-EV-Board Reference Design](#) (ZIP)
- [ESP32-P4 Series SoC Errata](#)
- [1.0K-GT-15PB Specification](#) (PDF)
- [Camera Datasheet](#) (PDF)
- [Display Datasheet](#) (PDF)
- [Datasheet of display driver chip EK73217BCGA](#) (PDF)
- [Datasheet of display driver chip EK79007AD](#) (PDF)
- [LCD Adapter Board Schematic](#) (PDF)
- [LCD Adapter Board PCB Layout](#) (PDF)
- [Camera Adapter Board Schematic](#) (PDF)
- [Camera Adapter Board PCB Layout](#) (PDF)

For further design documentation for the board, please contact us at sales@espressif.com.

¹ P: Power supply; I: Input; O: Output; T: High impedance.

² GPIO0 and GPIO1 can be enabled by disabling the XTAL_32K function, which can be achieved by moving R61 and R59 to R199 and R197, respectively.

³ GPIO45 can be enabled by disabling the SD_PWRn function, which can be achieved by moving R231 to R100.

Chapter 2

ESP32-P4X-EYE

ESP32-P4X-EYE is a vision development board based on the ESP32-P4 chip, mainly targeting camera applications. You can find examples for ESP32-P4X-EYE by accessing [Examples](#) .

2.1 ESP32-P4X-EYE

This user guide will help you get started with ESP32-P4X-EYE and will also provide more in-depth information.

ESP32-P4X-EYE is a vision development board based on the ESP32-P4 chip, mainly targeting camera applications. ESP32-P4 features a dual-core RISC-V processor and supports up to 32 MB of PSRAM. In addition, ESP32-P4 supports USB 2.0 standard, MIPI-CSI/DSI, H264 Encoder, and various other peripherals. With all of its outstanding features, the board is an ideal choice for developing low-cost, high-performance, low-power network-connected audio and video products.

The board integrates the ESP32-C6-MINI-1U module for Wi-Fi and Bluetooth communication. It supports MIPI-CSI camera interface and USB 2.0 High-Speed device mode. Rich onboard features include a camera, display, microphone, and MicroSD card, enabling real-time monitoring of the environment and collection of image and audio data. It is suitable for applications such as smart surveillance cameras, vision model detection, and edge computing in IoT that require real-time image processing and wireless communication.

Most of the I/O pins are broken out to the pin header for easy interfacing. Developers can connect peripherals with jumper wires.

This guide includes the following sections:

- *Getting Started*: Overview of ESP32-P4X-EYE and hardware/software setup instructions to get started.
- *Hardware Reference*: More detailed information about the ESP32-P4X-EYE' s hardware.
- *Hardware Revision Details*: Revision history, known issues, and links to user guides for previous versions (if any) of ESP32-P4X-EYE.
- *Related Documents*: Links to related documentation.

2.1.1 Getting Started

This section provides a brief introduction to ESP32-P4X-EYE, instructions on how to do the initial hardware setup and how to flash firmware onto it.



Fig. 1: ESP32-P4X-EYE Front View (click to enlarge)



Fig. 2: ESP32-P4X-EYE Back View (click to enlarge)




Fig. 3: ESP32-P4X-EYE PCB Top View (click to enlarge)




Fig. 4: ESP32-P4X-EYE Front View (click to enlarge)

Description of Components

The key components of the top PCB are described in a clockwise direction. To facilitate use, these components or interfaces are also marked on the ESP32-P4X-EYE enclosure.

Key Component	Description
MicroSD Card Slot	Supports a MicroSD card through 4-line SD bus with SDIO protocol or SPI protocol.
Test Points	Provides access points for programming and testing the ESP32-C6-MINI-1U; can be connected via Dupont wires.
USB 2.0 Device Port	Connected to the USB 2.0 OTG High-Speed interface of ESP32-P4, compliant with the USB 2.0 specification. When communicating with other devices via this port, ESP32-P4 acts as a USB device connecting to a USB host. USB 2.0 Device Port can also be used for powering the board. Marked with <code>USB 2.0</code> on the enclosure.
USB Debug Port	Used for board power, firmware flashing, and connecting to USB-Serial-JTAG interface of ESP32-P4. Marked with <code>Debug</code> on the enclosure.
Power Switch	Flip to “I” to power on the board with 5 V input; flip to “O” to power off.
User-defined Buttons	Customizable by user application.
LCD FPC Connector	Connects to a 1.54-inch LCD screen.
LCD	1.54-inch LCD with 240 × 240 resolution and SPI interface, capable of displaying real-time images from the camera. For details, refer to Display Datasheet .
Charging Indicator	When the battery is charging, the indicator light is red; once charging is complete, the light turns green.




Fig. 5: ESP32-P4X-EYE PCB Bottom View (click to enlarge)

The key components of the back PCB are described in a clockwise direction. To facilitate use, these components or interfaces are also marked on the ESP32-P4X-EYE enclosure.




Fig. 6: ESP32-P4X-EYE Back View (click to enlarge)

Key Component	Description
Rotary Encoder	You can customize functions based on your application, such as using it to control LCD interface or adjust camera zoom levels.
ESP32-C6-MINI-1U	Serves as the Wi-Fi and Bluetooth communication module.
Fill Light	Provides illumination for image capture and video recording.
Digital Microphone	Used for voice recognition or audio recording.
MIPI CSI Connector	Connects to the camera module.
Female Header	2 x 10P header, customizable based on application.
SPI flash	16 MB flash connected via the SPI interface.
ESP32-P4	High-performance MCU with large internal memory; supports advanced image and voice processing.
Battery Connector	Connects to a lithium battery.
Reset Button	Resets the board. Marked with  on the enclosure.
Boot Button	Controls boot mode. Marked with  on the enclosure. Press the Reset Button while holding down the Boot Button to reset ESP32-P4 and enter firmware download mode. Firmware can then be downloaded to SPI flash via the USB Debug Port. In general applications, it can act as a confirmation button.
Camera	2 MP resolution with manually adjustable focal length. For details, refer to Camera Datasheet .

Application Examples

The following application examples are available for ESP32-P4X-EYE:

- [Factory Demo](#) - Demonstrates a comprehensive mini camera application for ESP32-P4X-EYE that supports photo capture, timed capture, video recording, album preview, USB SD card mounting, image parameter configuration, and AI features including face detection, pedestrian detection, and YOLOv11-nano-based object detection.

For more examples and the latest updates, please refer to the [examples](#) folder.

To explore the application examples or to develop your own, please follow the steps outlined in the [Application Development](#) section.

Application Development

Before powering up your ESP32-P4X-EYE, please make sure that it is in good condition with no obvious signs of damage.

Required Hardware

- ESP32-P4X-EYE
- USB cables
- Computer running Windows, Linux, or macOS

Note: Be sure to use a good quality USB cable. Some cables are for charging only and do not provide the needed data lines nor work for programming the boards.

Optional Hardware

- MicroSD card
- Lithium battery

Hardware Setup Connect ESP32-P4X-EYE to your computer using a USB cable. The board can be powered through the USB 2.0 Device Port or USB Debug Port. The USB Debug Port is recommended for flashing firmware and debugging.

Software Setup To set up your development environment and flash an application example onto your board, please follow the [installation instructions](#) in [ESP-IDF Get Started](#).

2.1.2 Hardware Reference

Functional Block Diagram

The block diagram below shows the components of ESP32-P4X-EYE and their interconnections.




Fig. 7: ESP32-P4X-EYE Functional Block Diagram (click to enlarge)

Power Supply Options

ESP32-P4X-EYE can be powered using the following methods:

1. Via the USB 2.0 Device Port or USB Debug Port

Connect ESP32-P4X-EYE to a power source using a USB Type-C cable through either of the two ports. If a lithium battery is already installed, it will be charged simultaneously.

2. Via the Battery Connector

To use this method, first open the enclosure, then connect the battery to the Battery Connector. The lithium battery must not exceed 4 mm × 25 mm × 45 mm in size. It should use a 1.25 mm pitch connector, and the polarity must match the markings on the PCB.

Female Header

USB 2.0 Device Port Circuit




Fig. 8: Battery Connection (click to enlarge)




Fig. 9: Female Header (click to enlarge)




Fig. 10: USB 2.0 Device Port Circuit (click to enlarge)

LCD Circuit

Please note that this interface supports SPI displays. ESP32-P4X-EYE features the [ST7789](#), which uses the `LC_D_B` pin (GPIO20) to control the backlight.

MicroSD Card Slot Interface Circuit

Please note that the MicroSD card interface supports:

- 1-bit and 4-bit SD bus configurations
- Communication via SDIO protocol or SPI protocol

Charging Circuit

Microphone Circuit

Camera Circuit

Rotary Encoder Circuit

ESP32-C6-MINI-1U Module Circuit

2.1.3 Hardware Revision Details

The difference between the ESP32-P4X-EYE and the *ESP32-P4-EYE* is that the main chip on the former has been upgraded to the ESP32-P4 chip revision v3.1 or later version.

2.1.4 Related Documents

Please download the following documents from [the HTML version of esp-dev-kits Documentation](#).

- [ESP32-P4X-EYE Reference Design \(ZIP\)](#)
- [Camera Datasheet \(PDF\)](#)
- [Display Datasheet \(PDF\)](#)

27

[Submit Document Feedback](#)




Fig. 11: LCD Circuit (click to enlarge)

MicroSD Card:




Fig. 12: MicroSD Card Slot Interface Circuit (click to enlarge)

Camera Connector:




Fig. 15: Camera Circuit (click to enlarge)





Fig. 16: Rotary Encoder Circuit (click to enlarge)

30

Submit Document Feedback



- [ST7789VW Datasheet \(PDF\)](#)
- [OV2710 Overview \(PDF\)](#)

Chapter 3

EOL (End of Life) Boards

This section contains user guides for the ESP32-P4 end-of-life development boards and is provided for reference only. While these boards may still be available on the market or used in legacy systems, they no longer receive updates, bug fixes, or official support. It is recommended to switch to newer development boards for better performance and more features.

3.1 ESP32-P4-Function-EV-Board

ESP32-P4-Function-EV-Board is a multimedia development board based on the ESP32-P4 chip. ESP32-P4 chip features a dual-core RISC-V processor and supports up to 32 MB PSRAM. In addition, ESP32-P4 supports USB 2.0 specification, MIPI-CSI/DSI, H264 Encoder, and various other peripherals. With all of its outstanding features, the board is an ideal choice for developing low-cost, high-performance, low-power network-connected audio and video products.

3.1.1 ESP32-P4-Function-EV-Board v1.5.2

The older version: [ESP32-P4-Function-EV-Board v1.4](#)

Note: If you are using ESP32-P4X-Function-EV-Board with chip revision v3.x, please refer to this [user guide](#).

The version number v1.5.2 refers to the board hardware version. To identify the embedded chip revision, refer to [ESP32-P4 Series SoC Errata](#) > [Chip Revision Identification](#).

This user guide will help you get started with ESP32-P4-Function-EV-Board and will also provide more in-depth information.

ESP32-P4-Function-EV-Board is a multimedia development board based on the ESP32-P4 chip. ESP32-P4 chip features a dual-core RISC-V processor and supports up to 32 MB PSRAM. In addition, ESP32-P4 supports USB 2.0 specification, MIPI-CSI/DSI, H264 Encoder, and various other peripherals. With all of its outstanding features, the board is an ideal choice for developing low-cost, high-performance, low-power network-connected audio and video products.

The 2.4 GHz Wi-Fi 6 & Bluetooth 5 (LE) module ESP32-C6-MINI-1 serves as the Wi-Fi and Bluetooth module of the board. The board also includes a 7-inch capacitive touch screen with a resolution of 1024 x 600 and a 2MP camera with MIPI CSI, enriching the user interaction experience. The development board is suitable for prototyping

a wide range of products, including visual doorbells, network cameras, smart home central control screens, LCD electronic price tags, two-wheel vehicle dashboards, etc.

Most of the I/O pins are broken out to the pin headers for easy interfacing. Developers can connect peripherals with jumper wires.




Fig. 1: ESP32-P4-Function-EV-Board

The document consists of the following major sections:

- [Getting Started](#): Overview of ESP32-P4-Function-EV-Board and hardware/software setup instructions to get started.
- [Hardware Reference](#): More detailed information about the ESP32-P4-Function-EV-Board's hardware.
- [Hardware Revision Details](#): Revision history, known issues, and links to user guides for previous versions (if any) of ESP32-P4-Function-EV-Board.
- [Related Documents](#): Links to related documentation.

Getting Started

This section provides a brief introduction to ESP32-P4-Function-EV-Board, instructions on how to do the initial hardware setup and how to flash firmware onto it.

Description of Components The key components of the board are described from front view to back view, starting from the J1, in a clockwise direction.




Fig. 2: ESP32-P4-Function-EV-Board - front (click to enlarge)




Fig. 3: ESP32-P4-Function-EV-Board - back (click to enlarge)

No.	Key Component	Description
1	J1	All available GPIO pins are broken out to the header block J1 for easy interfacing. For more details, see Header Block .
2	ESP32-C6 Module Programming Connector	The connector can be used with ESP-Prog or other UART tools to flash firmware onto the ESP32-C6 module.
3	ESP32-C6-MINI-1 Module	This module serves as the Wi-Fi and Bluetooth communication module for the board.
4	Microphone	Onboard microphone connected to the interface of Audio Codec Chip.
5	Reset Button	Resets the board.
6	Audio Codec Chip	ES8311 is a low-power mono audio codec chip. It includes a single-channel ADC, a single-channel DAC, a low-noise pre-amplifier, a headphone driver, digital sound effects, analog mixing, and gain functions. It interfaces with the ESP32-P4 chip over I2S and I2C buses to provide hardware audio processing independent of the audio application.
7	Speaker Output Port	This port is used to connect a speaker. The maximum output power can drive a 4 Ω , 3 W speaker. The pin spacing is 2.00 mm (0.08").
8	Audio PA Chip	NS4150B is an EMI-compliant, 3 W mono Class D audio power amplifier that amplifies audio signals from the audio codec chip to drive speakers.
9	5 V to 3.3 V LDO	A power regulator that converts a 5 V supply to a 3.3 V output.
10	BOOT Button	The boot mode control button. Press the Reset Button while holding down the Boot Button to reset ESP32-P4 and enter firmware download mode. Firmware can then be downloaded to SPI flash via the USB Serial/JTAG Port.
11	Ethernet PHY IC	Ethernet PHY chip connected to the ESP32-P4 EMAC RMII interface and RJ45 Ethernet Port.
12	Buck Converter	A buck DC-DC converter for the 3.3 V power supply.
13	5 V Power-on LED	This LED lights up when the board is powered through any USB Type-C port.
14	RJ45 Ethernet Port	An Ethernet Port supporting 10/100 Mbps adaptive.

No.	Key Component		Description
15	USB Port	Full-speed	USB Type-C port that supports USB 2.0 Full-speed data rate. It can be used as the power supply interface for the development board and as a communication interface.
16	USB Port	Serial/JTAG	USB Type-C port that supports USB 2.0 Full-speed data rate. It can be used to flash firmware to the ESP32-P4 chip, communicate with the chip via the USB protocol, and perform JTAG debugging.
17	USB Port	2.0 Type-C	The USB 2.0 Type-C Port is connected to the USB 2.0 OTG High-Speed interface of ESP32-P4, compliant with the USB 2.0 specification. When communicating with other devices via this port, ESP32-P4 acts as a USB device connecting to a USB host. Please note that USB 2.0 Type-C Port and USB 2.0 Type-A Port cannot be used simultaneously. USB 2.0 Type-C Port can also be used for powering the board.
18	USB Port	2.0 Type-A	The USB 2.0 Type-A Port is connected to the USB 2.0 OTG High-Speed interface of ESP32-P4, compliant with the USB 2.0 specification. When communicating with other devices via this port, ESP32-P4 acts as a USB host, providing up to 500 mA of current. Please note that USB 2.0 Type-C Port and USB 2.0 Type-A Port cannot be used simultaneously.
19	Power Switch		Power On/Off Switch. Toggling toward the ON sign powers the board on (5 V), toggling away from the ON sign powers the board off.
20	Switch		TPS2051C is a USB power switch that provides a 500 mA output current limit.
21	MIPI CSI	Connector	The FPC connector 1.0K-GT-15PB is used for connecting external camera modules to enable image transmission. For details, please refer to 1.0K-GT-15PB specification in Related Documents. FPC specifications: 1.0 mm pitch, 0.7 mm pin width, 0.3 mm thickness, 15 pins.
22	Buck Converter		A buck DC-DC converter for VDD_HP power supply of ESP32-P4.
23	ESP32-P4		A high-performance MCU with large internal memory and powerful image and voice processing capabilities.
24	40 MHz XTAL		An external precision 40 MHz crystal oscillator that serves as a clock for the system.
25	32.768 kHz XTAL		An external precision 32.768 kHz crystal oscillator that serves as a low-power clock while the chip is in deep-sleep mode.
26	MIPI DSI	Connector	The FPC connector 1.0K-GT-15PB is used for connecting displays. For details, please refer to 1.0K-GT-15PB Specification in Related Documents. FPC specifications: 1.0 mm pitch, 0.7 mm pin width, 0.3 mm thickness, 15 pins.
27	SPI flash		The 16 MB flash is connected to the chip via the SPI interface.
28	MicroSD Card Slot		The development board supports a MicroSD card in 4-bit mode and can store or play audio files from the MicroSD card.

Accessories Optionally, the following accessories are included in the package:

- LCD and its accessories (optional)
 - 7-inch capacitive touch screen with a resolution of 1024 x 600
 - LCD adapter board
 - Accessories bag, including DuPont wires, ribbon cable for LCD, long standoffs (20 mm in length), and short standoffs (8 mm in length)
- Camera and its accessories (optional)
 - 2MP camera with MIPI CSI
 - Camera adapter board
 - Ribbon cable for camera

Note: Please note that the ribbon cable in the **forward direction**, whose strips at the two ends are on the same side, should be used for the **camera**; the ribbon cable in the **reverse direction**, whose strips at the two ends are on different sides, should be used for the **LCD**.




Fig. 4: Ribbon Cables in Forward and Reverse Directions

Application Examples The following application examples are available for ESP32-P4-Function-EV-Board v1.5.2:

- [ESP_Brookesia Phone](#) - Demonstrates an Android-like interface with multiple applications using ESP_Brookesia, utilizing MIPI-DSI, MIPI-CSI, ESP32-C6, SD card, and audio interfaces on a development board, providing a basis for efficient multimedia application development.
- [LVGL Demo v8](#) - Demonstrates how to port LVGL v8 and conduct performance testing using LVGL's built-in demos on an ESP32-P4-Function-EV-Board with a 7-inch LCD screen, serving as a foundation for developing applications based on LVGL v8.
- [LVGL Demo v9](#) - Demonstrates how to port LVGL v9 and conduct performance testing using LVGL's built-in demos on an ESP32-P4-Function-EV-Board, serving as a basis for developing applications based on LVGL v9.

For more examples and the latest updates, please refer to the [examples](#) folder.

To explore the application examples or to develop your own, please follow the steps outlined in the [Start Application Development](#) section.

Start Application Development Before powering up your ESP32-P4-Function-EV-Board, please make sure that it is in good condition with no obvious signs of damage.

Required Hardware

- ESP32-P4-Function-EV-Board
- USB cables
- Computer running Windows, Linux, or macOS

Note: Be sure to use a good quality USB cable. Some cables are for charging only and do not provide the needed data lines nor work for programming the boards.

Optional Hardware

- MicroSD card

Hardware Setup Connect the ESP32-P4-Function-EV-Board to your computer using a USB cable. The board can be powered through any of the USB Type-C ports. The USB Serial/JTAG Port is recommended for flashing firmware and debugging.

To connect the LCD, follow these steps:

1. Secure the development board to the LCD adapter board by attaching the short brass standoffs (8 mm in length) to the four standoff posts at the center of the LCD adapter board.
2. Connect the J3 header of the LCD adapter board to the MIPI DSI connector on the ESP32-P4-Function-EV-Board using the LCD ribbon cable (**reverse direction**). Note that the LCD adapter board is already connected to the LCD.
3. Use a DuPont wire to connect the RST_LCD pin of the J6 header of the LCD adapter board to the GPIO27 pin of the J1 header on the ESP32-P4-Function-EV-Board. The RST_LCD pin can be configured via software, with GPIO27 set as the default.
4. Use a DuPont wire to connect the PWM pin of the J6 header of the LCD adapter board to the GPIO26 pin of the J1 header on the ESP32-P4-Function-EV-Board. The PWM pin can be configured via software, with GPIO26 set as the default.
5. It is recommended to power the LCD by connecting a USB cable to the J1 header of the LCD adapter board. If this is not feasible, connect the 5V and GND pins of the LCD adapter board to corresponding pins on the J1 header of the ESP32-P4-Function-EV-Board, provided that the development board has sufficient power supply.
6. Attach the long brass standoffs (20 mm in length) to the four standoff posts on the periphery of the LCD adapter board to allow the LCD to stand upright.

In summary, the LCD adapter board and ESP32-P4-Function-EV-Board are connected via the following pins:

LCD Adapter Board	ESP32-P4-Function-EV
J3 header	MIPI DSI connector
RST_LCD pin of J6 header	GPIO27 pin of J1 header
PWM pin of J6 header	GPIO26 pin of J1 header
5V pin of J6 header	5V pin of J1 header
GND pin of J6 header	GND pin of J1 header

Note:

- If you power the LCD adapter board by connecting a USB cable to its J1 header, you do not need to connect its 5V and GND pins to the corresponding pins on the development board.
- To use the camera, connect the camera adapter board to the MIPI CSI connector on the development board using the camera ribbon cable (**forward direction**).

Software Setup To set up your development environment and flash an application example onto your board, please follow the instructions in [ESP-IDF Get Started](#).

Hardware Reference

Block Diagram The block diagram below shows the components of ESP32-P4-Function-EV-Board and their interconnections.

Power Supply Options Power can be supplied through any of the following ports:

- USB 2.0 Type-C Port
- USB Full-speed Port
- USB Serial/JTAG Port

If the USB cable used for debugging cannot provide enough current, you can connect the board to a power adapter via any available USB Type-C port.




Fig. 5: ESP32-P4-Function-EV-Board Block Diagram (click to enlarge)

Header Block The tables below provide the **Name** and **Function** of the pin header J1 of the board. The pin header names are shown in Figure [ESP32-P4-Function-EV-Board - front \(click to enlarge\)](#). The numbering is the same as in the [ESP32-P4-Function-EV-Board Schematic](#).

No.	Name	Type	Function
1	3V3	P	3.3 V power supply
2	5V	P	5 V power supply
3	7	I/O/T	GPIO7
4	5V	P	5 V power supply
5	8	I/O/T	GPIO8
6	GND	GND	Ground
7	23	I/O/T	GPIO23
8	37	I/O/T	U0TXD, GPIO37
9	GND	GND	Ground
10	38	I/O/T	U0RXD, GPIO38
11	21	I/O/T	GPIO21
12	22	I/O/T	GPIO22
13	20	I/O/T	GPIO20
14	GND	GND	Ground
15	6	I/O/T	GPIO6
16	5	I/O/T	GPIO5
17	3V3	P	3.3 V power supply
18	4	I/O/T	GPIO4
19	3	I/O/T	GPIO3
20	GND	GND	Ground

continues on next page

Table 1 – continued from previous page

No.	Name	Type ^{Page 39, 1}	Function
21	2	I/O/T	GPIO2
22	NC(1)	I/O/T	GPIO1 ²
23	NC(0)	I/O/T	GPIO0 ²
24	36	I/O/T	GPIO36
25	GND	GND	Ground
26	32	I/O/T	GPIO32
27	NC	–	No connection
28	NC	–	No connection
29	33	I/O/T	GPIO33
30	GND	GND	Ground
31	26	I/O/T	GPIO26
32	54	I/O/T	GPIO54
33	48	I/O/T	GPIO48
34	GND	GND	Ground
35	53	I/O/T	GPIO53
36	46	I/O/T	GPIO46
37	47	I/O/T	GPIO47
38	27	I/O/T	GPIO27
39	GND	GND	Ground
40	NC(45)	I/O/T	GPIO45 ³

J1

Hardware Revision Details

Initial release

Note: The main improvements in development board version v1.52 compared to v1.4 include: replacing the USB-to-UART Type-C port used for debugging with the ESP32-P4 chip's built-in USB Serial/JTAG port, adding a Full-speed USB OTG breakout to a Type-C port, and removing IO24 and IO25 from the pin headers.

Related Documents

Please download the following documents from [the HTML version of esp-dev-kits Documentation](#).

- [ESP32-P4-Function-EV-Board Schematic](#) (PDF)
- [ESP32-P4-Function-EV-Board PCB Layout](#) (PDF)
- [ESP32-P4-Function-EV-Board Assembly](#) (PDF)
- [ESP32-P4-Function-EV-Board Dimensions](#) (PDF)
- [ESP32-P4-Function-EV-Board Dimensions source file](#) (DXF) - You can view it with [Autodesk Viewer](#) online
- [1.0K-GT-15PB Specification](#) (PDF)
- [Camera Datasheet](#) (PDF)
- [Display Datasheet](#) (PDF)
- [Datasheet of display driver chip EK73217BCGA](#) (PDF)
- [Datasheet of display driver chip EK79007AD](#) (PDF)
- [LCD Adapter Board Schematic](#) (PDF)
- [LCD Adapter Board PCB Layout](#) (PDF)
- [Camera Adapter Board Schematic](#) (PDF)
- [Camera Adapter Board PCB Layout](#) (PDF)

¹ P: Power supply; I: Input; O: Output; T: High impedance.

² GPIO0 and GPIO1 can be enabled by disabling the XTAL_32K function, which can be achieved by moving R61 and R59 to R199 and R197, respectively.

³ GPIO45 can be enabled by disabling the SD_PWRn function, which can be achieved by moving R231 to R100.

For further design documentation for the board, please contact us at sales@espressif.com.

ESP32-P4-Function-EV-Board v1.4

New version available: [ESP32-P4-Function-EV-Board v1.5.2](#)

Note: If you are using ESP32-P4X-Function-EV-Board with chip revision v3.x, please refer to this [user guide](#).

The version number v1.4 refers to the board hardware version. To identify the embedded chip revision, refer to [ESP32-P4 Series SoC Errata](#) > [Chip Revision Identification](#).

This user guide will help you get started with ESP32-P4-Function-EV-Board and will also provide more in-depth information.

ESP32-P4-Function-EV-Board is a multimedia development board based on the ESP32-P4 chip. ESP32-P4 chip features a dual-core RISC-V processor and supports up to 32 MB PSRAM. In addition, ESP32-P4 supports USB 2.0 specification, MIPI-CSI/DSI, H264 Encoder, and various other peripherals. With all of its outstanding features, the board is an ideal choice for developing low-cost, high-performance, low-power network-connected audio and video products.

The 2.4 GHz Wi-Fi 6 & Bluetooth 5 (LE) module ESP32-C6-MINI-1 serves as the Wi-Fi and Bluetooth module of the board. The board also includes a 7-inch capacitive touch screen with a resolution of 1024 x 600 and a 2MP camera with MIPI CSI, enriching the user interaction experience. The development board is suitable for prototyping a wide range of products, including visual doorbells, network cameras, smart home central control screens, LCD electronic price tags, two-wheel vehicle dashboards, etc.

Most of the I/O pins are broken out to the pin headers for easy interfacing. Developers can connect peripherals with jumper wires.

The document consists of the following major sections:

- [Getting Started](#): Overview of ESP32-P4-Function-EV-Board and hardware/software setup instructions to get started.
- [Hardware Reference](#): More detailed information about the ESP32-P4-Function-EV-Board's hardware.
- [Hardware Revision Details](#): Revision history, known issues, and links to user guides for previous versions (if any) of ESP32-P4-Function-EV-Board.
- [Related Documents](#): Links to related documentation.

Getting Started This section provides a brief introduction to ESP32-P4-Function-EV-Board, instructions on how to do the initial hardware setup and how to flash firmware onto it.

Description of Components The key components of the board are described in a clockwise direction.



Fig. 6: ESP32-P4-Function-EV-Board




Fig. 7: ESP32-P4-Function-EV-Board - front (click to enlarge)




Fig. 8: ESP32-P4-Function-EV-Board - back (click to enlarge)

Key Component	Description
J1	All available GPIO pins are broken out to the header block J1 for easy interfacing. For more details, see Header Block .
ESP32-C6 Module Programming Connector	The connector can be used with ESP-Prog or other UART tools to flash firmware onto the ESP32-C6 module.
ESP32-C6-MINI-1 Module	This module serves as the Wi-Fi and Bluetooth communication module for the board.
Microphone	Onboard microphone connected to the interface of Audio Codec Chip.
Reset Button	Resets the board.
Audio Codec Chip	ES8311 is a low-power mono audio codec chip. It includes a single-channel ADC, a single-channel DAC, a low-noise pre-amplifier, a headphone driver, digital sound effects, analog mixing, and gain functions. It interfaces with the ESP32-P4 chip over I2S and I2C buses to provide hardware audio processing independent of the audio application.
Speaker Output Port	This port is used to connect a speaker. The maximum output power can drive a 4 Ω , 3 W speaker. The pin spacing is 2.00 mm (0.08").
Audio PA Chip	NS4150B is an EMI-compliant, 3 W mono Class D audio power amplifier that amplifies audio signals from the audio codec chip to drive speakers.
5 V to 3.3 V LDO	A power regulator that converts a 5 V supply to a 3.3 V output.
BOOT Button	The boot mode control button. Press the Reset Button while holding down the Boot Button to reset ESP32-P4 and enter firmware download mode. Firmware can then be downloaded to SPI flash via the USB-to-UART Port.
Ethernet PHY IC	Ethernet PHY chip connected to the ESP32-P4 EMAC RMII interface and RJ45 Ethernet Port.
Buck Converter	A buck DC-DC converter for the 3.3 V power supply.
USB-to-UART Bridge Chip	CP2102N is a single USB-to-UART bridge chip connected to the ESP32-P4 UART0 interface, CHIP_PU, and GPIO35 (strapping pin). It provides transfer rates up to 3 Mbps for firmware downloading and debugging, supporting the automatic download functionality.
5 V Power-on LED	This LED lights up when the board is powered through any USB Type-C port.
RJ45 Ethernet Port	An Ethernet Port supporting 10/100 Mbps adaptive.
USB-to-UART Port	The USB Type-C port can be used to power the board, flash firmware to the chip, and communicate with the ESP32-P4 chip via the USB-to-UART Bridge Chip.
USB Power-in Port	The USB Type-C port used to power the board.
USB 2.0 Type-C Port	The USB 2.0 Type-C Port is connected to the USB 2.0 OTG High-Speed interface of ESP32-P4, compliant with the USB 2.0 specification. When communicating with other devices via this port, ESP32-P4 acts as a USB device connecting to a USB host. Please note that USB 2.0 Type-C Port and USB 2.0 Type-A Port cannot be used simultaneously. USB 2.0 Type-C Port can also be used for powering the board.
USB 2.0 Type-A Port	The USB 2.0 Type-A Port is connected to the USB 2.0 OTG High-Speed interface of ESP32-P4, compliant with the USB 2.0 specification. When communicating with other devices via this port, ESP32-P4 acts as a USB host, providing up to 500 mA of current. Please note that USB 2.0 Type-C Port and USB 2.0 Type-A Port cannot be used simultaneously.

Key Component	Description
Power Switch	Power On/Off Switch. Toggling toward the ON sign powers the board on (5 V), toggling away from the ON sign powers the board off.
Switch	TPS2051C is a USB power switch that provides a 500 mA output current limit.
MIPI CSI Connector	The FPC connector 1.0K-GT-15PB is used for connecting external camera modules to enable image transmission. For details, please refer to 1.0K-GT-15PB specification in Related Documents. FPC specifications: 1.0 mm pitch, 0.7 mm pin width, 0.3 mm thickness, 15 pins.
Buck Converter	A buck DC-DC converter for VDD_HP power supply of ESP32-P4.
ESP32-P4	A high-performance MCU with large internal memory and powerful image and voice processing capabilities.
40 MHz XTAL	An external precision 40 MHz crystal oscillator that serves as a clock for the system.
32.768 kHz XTAL	An external precision 32.768 kHz crystal oscillator that serves as a low-power clock while the chip is in deep-sleep mode.
MIPI DSI Connector	The FPC connector 1.0K-GT-15PB is used for connecting displays. For details, please refer to 1.0K-GT-15PB Specification in Related Documents. FPC specifications: 1.0 mm pitch, 0.7 mm pin width, 0.3 mm thickness, 15 pins.
SPI flash	The 16 MB flash is connected to the chip via the SPI interface.
MicroSD Card Slot	The development board supports a MicroSD card in 4-bit mode and can store or play audio files from the MicroSD card.

Accessories Optionally, the following accessories are included in the package:

- LCD and its accessories (optional)
 - 7-inch capacitive touch screen with a resolution of 1024 x 600
 - LCD adapter board
 - Accessories bag, including DuPont wires, ribbon cable for LCD, long standoffs (20 mm in length), and short standoffs (8 mm in length)
- Camera and its accessories (optional)
 - 2MP camera with MIPI CSI
 - Camera adapter board
 - Ribbon cable for camera




Fig. 9: Ribbon Cables in Forward and Reverse Directions

Note: Please note that the ribbon cable in the **forward direction**, whose strips at the two ends are on the same side, should be used for the **camera**; the ribbon cable in the **reverse direction**, whose strips at the two ends are on different sides, should be used for the **LCD**.

Application Examples The following application examples are available for ESP32-P4-Function-EV-Board v1.4:

- [ESP_Brookesia Phone](#) - Demonstrates an Android-like interface with multiple applications using ESP_Brookesia, utilizing MIPI-DSI, MIPI-CSI, ESP32-C6, SD card, and audio interfaces on a development board, providing a basis for efficient multimedia application development.
- [LVGL Demo v8](#) - Demonstrates how to port LVGL v8 and conduct performance testing using LVGL's built-in demos on an ESP32-P4-Function-EV-Board with a 7-inch LCD screen, serving as a foundation for developing applications based on LVGL v8.
- [LVGL Demo v9](#) - Demonstrates how to port LVGL v9 and conduct performance testing using LVGL's built-in demos on an ESP32-P4-Function-EV-Board, serving as a basis for developing applications based on LVGL v9.

For more examples and the latest updates, please refer to the [examples](#) folder.

To explore the application examples or to develop your own, please follow the steps outlined in the [Start Application Development](#) section.

Start Application Development Before powering up your ESP32-P4-Function-EV-Board, please make sure that it is in good condition with no obvious signs of damage.

Required Hardware

- ESP32-P4-Function-EV-Board
- USB cables
- Computer running Windows, Linux, or macOS

Note: Be sure to use a good quality USB cable. Some cables are for charging only and do not provide the needed data lines nor work for programming the boards.

Optional Hardware

- MicroSD card

Hardware Setup Connect the ESP32-P4-Function-EV-Board to your computer using a USB cable. The board can be powered through any of the USB Type-C ports. The USB-to-UART Port is recommended for flashing firmware and debugging.

To connect the LCD, follow these steps:

1. Secure the development board to the LCD adapter board by attaching the short brass standoffs (8 mm in length) to the four standoff posts at the center of the LCD adapter board.
2. Connect the J3 header of the LCD adapter board to the MIPI DSI connector on the ESP32-P4-Function-EV-Board using the LCD ribbon cable (**reverse direction**). Note that the LCD adapter board is already connected to the LCD.
3. Use a DuPont wire to connect the RST_LCD pin of the J6 header of the LCD adapter board to the GPIO27 pin of the J1 header on the ESP32-P4-Function-EV-Board. The RST_LCD pin can be configured via software, with GPIO27 set as the default.
4. Use a DuPont wire to connect the PWM pin of the J6 header of the LCD adapter board to the GPIO26 pin of the J1 header on the ESP32-P4-Function-EV-Board. The PWM pin can be configured via software, with GPIO26 set as the default.

5. It is recommended to power the LCD by connecting a USB cable to the J1 header of the LCD adapter board. If this is not feasible, connect the 5V and GND pins of the LCD adapter board to corresponding pins on the J1 header of the ESP32-P4-Function-EV-Board, provided that the development board has sufficient power supply.
6. Attach the long brass standoffs (20 mm in length) to the four standoff posts on the periphery of the LCD adapter board to allow the LCD to stand upright.

In summary, the LCD adapter board and ESP32-P4-Function-EV-Board are connected via the following pins:

LCD Adapter Board	ESP32-P4-Function-EV
J3 header	MIPI DSI connector
RST_LCD pin of J6 header	GPIO27 pin of J1 header
PWM pin of J6 header	GPIO26 pin of J1 header
5V pin of J6 header	5V pin of J1 header
GND pin of J6 header	GND pin of J1 header

Note:

- If you power the LCD adapter board by connecting a USB cable to its J1 header, you do not need to connect its 5V and GND pins to the corresponding pins on the development board.
- To use the camera, connect the camera adapter board to the MIPI CSI connector on the development board using the camera ribbon cable (**forward direction**).

Software Setup To set up your development environment and flash an application example onto your board, please follow the instructions in [ESP-IDF Get Started](#).

Hardware Reference

Block Diagram The block diagram below shows the components of ESP32-P4-Function-EV-Board and their interconnections.

Power Supply Options Power can be supplied through any of the following ports:

- USB 2.0 Type-C Port
- USB Power-in Port
- USB-to-UART Port

If the USB cable used for debugging cannot provide enough current, you can connect the board to a power adapter via any available USB Type-C port.

Header Block The tables below provide the **Name** and **Function** of the pin header J1 of the board. The pin header names are shown in Figure [ESP32-P4-Function-EV-Board - front \(click to enlarge\)](#). The numbering is the same as in the [ESP32-P4-Function-EV-Board v1.4 Schematic](#).

No.	Name	Type Page 47, 1	Function
1	3V3	P	3.3 V power supply
2	5V	P	5 V power supply
3	7	I/O/T	GPIO7
4	5V	P	5 V power supply
5	8	I/O/T	GPIO8

continues on next page

Table 2 – continued from previous page

No.	Name	Type ^{Page 47, 1}	Function
6	GND	GND	Ground
7	23	I/O/T	GPIO23
8	37	I/O/T	U0TXD, GPIO37
9	GND	GND	Ground
10	38	I/O/T	U0RXD, GPIO38
11	21	I/O/T	GPIO21
12	22	I/O/T	GPIO22
13	20	I/O/T	GPIO20
14	GND	GND	Ground
15	6	I/O/T	GPIO6
16	5	I/O/T	GPIO5
17	3V3	P	3.3 V power supply
18	4	I/O/T	GPIO4
19	3	I/O/T	GPIO3
20	GND	GND	Ground
21	2	I/O/T	GPIO2
22	NC(1)	I/O/T	GPIO1 ²
23	NC(0)	I/O/T	GPIO0 ²
24	36	I/O/T	GPIO36
25	GND	GND	Ground
26	32	I/O/T	GPIO32
27	24	I/O/T	GPIO24
28	25	I/O/T	GPIO25
29	33	I/O/T	GPIO33
30	GND	GND	Ground
31	26	I/O/T	GPIO26
32	54	I/O/T	GPIO54
33	48	I/O/T	GPIO48
34	GND	GND	Ground
35	53	I/O/T	GPIO53
36	46	I/O/T	GPIO46
37	47	I/O/T	GPIO47
38	27	I/O/T	GPIO27
39	GND	GND	Ground
40	NC(45)	I/O/T	GPIO45 ³

J1

Hardware Revision Details No previous versions available.

Related Documents Please download the following documents from [the HTML version of esp-dev-kits Documentation](#).

- [ESP32-P4-Function-EV-Board v1.4 Schematic \(PDF\)](#)
- [ESP32-P4-Function-EV-Board v1.4 PCB Layout \(PDF\)](#)
- [ESP32-P4-Function-EV-Board v1.4 Dimensions \(PDF\)](#)
- [ESP32-P4-Function-EV-Board v1.4 Dimensions source file \(DXF\)](#) - You can view it with [Autodesk Viewer](#) online
- [1.0K-GT-15PB Specification \(PDF\)](#)
- [Camera Datasheet \(PDF\)](#)

¹ P: Power supply; I: Input; O: Output; T: High impedance.

² GPIO0 and GPIO1 can be enabled by disabling the XTAL_32K function, which can be achieved by moving R61 and R59 to R199 and R197, respectively.

³ GPIO45 can be enabled by disabling the SD_PWRn function, which can be achieved by moving R231 to R100.




Fig. 10: ESP32-P4-Function-EV-Board v1.4 (click to enlarge)

- [Display Datasheet \(PDF\)](#)
- [Datasheet of display driver chip EK73217BCGA \(PDF\)](#)
- [Datasheet of display driver chip EK79007AD \(PDF\)](#)
- [LCD Adapter Board Schematic \(PDF\)](#)
- [LCD Adapter Board PCB Layout \(PDF\)](#)
- [Camera Adapter Board Schematic \(PDF\)](#)
- [Camera Adapter Board PCB Layout \(PDF\)](#)

For further design documentation for the board, please contact us at sales@espressif.com.

3.2 ESP32-P4-EYE

ESP32-P4-EYE is a vision development board based on the ESP32-P4 chip, mainly targeting camera applications.

You can find examples for ESP32-P4-EYE by accessing [Examples](#).

3.2.1 ESP32-P4-EYE

Note: If you are using ESP32-P4X-EYE with chip revision v3.x, please refer to this [user guide](#).

To identify the embedded chip revision, refer to [ESP32-P4 Series SoC Errata > Chip Revision Identification](#).

This user guide will help you get started with ESP32-P4-EYE and will also provide more in-depth information.

ESP32-P4-EYE is a vision development board based on the ESP32-P4 chip, mainly targeting camera applications. ESP32-P4 features a dual-core RISC-V processor and supports up to 32 MB of PSRAM. In addition, ESP32-P4 supports USB 2.0 standard, MIPI-CSI/DSI, H264 Encoder, and various other peripherals. With all of its outstanding

features, the board is an ideal choice for developing low-cost, high-performance, low-power network-connected audio and video products.

The board integrates the ESP32-C6-MINI-1U module for Wi-Fi and Bluetooth communication. It supports MIPI-CSI camera interface and USB 2.0 High-Speed device mode. Rich onboard features include a camera, display, microphone, and MicroSD card, enabling real-time monitoring of the environment and collection of image and audio data. It is suitable for applications such as smart surveillance cameras, vision model detection, and edge computing in IoT that require real-time image processing and wireless communication.

Most of the I/O pins are broken out to the pin header for easy interfacing. Developers can connect peripherals with jumper wires.



Fig. 11: ESP32-P4-EYE Front View (click to enlarge)

This guide includes the following sections:

- [Getting Started](#): Overview of ESP32-P4-EYE and hardware/software setup instructions to get started.
- [Hardware Reference](#): More detailed information about the ESP32-P4-EYE's hardware.
- [Hardware Revision Details](#): Revision history, known issues, and links to user guides for previous versions (if any) of ESP32-P4-EYE.
- [Related Documents](#): Links to related documentation.

Getting Started

This section provides a brief introduction to ESP32-P4-EYE, instructions on how to do the initial hardware setup and how to flash firmware onto it.



Fig. 12: ESP32-P4-EYE Back View (click to enlarge)




Fig. 13: ESP32-P4-EYE PCB Top View (click to enlarge)

Description of Components The key components of the top PCB are described in a clockwise direction. To facilitate use, these components or interfaces are also marked on the ESP32-P4-EYE enclosure.

Key Component	Description
MicroSD Card Slot	Supports a MicroSD card through 4-line SD bus with SDIO protocol or SPI protocol.
Test Points	Provides access points for programming and testing the ESP32-C6-MINI-1U; can be connected via Dupont wires.
USB 2.0 Device Port	Connected to the USB 2.0 OTG High-Speed interface of ESP32-P4, compliant with the USB 2.0 specification. When communicating with other devices via this port, ESP32-P4 acts as a USB device connecting to a USB host. USB 2.0 Device Port can also be used for powering the board. Marked with USB 2.0 on the enclosure.
USB Debug Port	Used for board power, firmware flashing, and connecting to USB-Serial-JTAG interface of ESP32-P4. Marked with Debug on the enclosure.
Power Switch	Flip to “I” to power on the board with 5 V input; flip to “O” to power off.
User-defined Buttons	Customizable by user application.
LCD FPC Connector	Connects to a 1.54-inch LCD screen.
LCD	1.54-inch LCD with 240 × 240 resolution and SPI interface, capable of displaying real-time images from the camera. For details, refer to Display Datasheet .
Charging Indicator	When the battery is charging, the indicator light is red; once charging is complete, the light turns green.

The key components of the back PCB are described in a clockwise direction. To facilitate use, these components or interfaces are also marked on the ESP32-P4-EYE enclosure.




Fig. 14: ESP32-P4-EYE Front View (click to enlarge)




Fig. 15: ESP32-P4-EYE PCB Bottom View (click to enlarge)




Fig. 16: ESP32-P4-EYE Back View (click to enlarge)

Key Component	Description
Rotary Encoder	You can customize functions based on your application, such as using it to control LCD interface or adjust camera zoom levels.
ESP32-C6-MINI-1U	Serves as the Wi-Fi and Bluetooth communication module.
Fill Light	Provides illumination for image capture and video recording.
Digital Microphone	Used for voice recognition or audio recording.
MIPI CSI Connector	Connects to the camera module.
Female Header	2 x 10P header, customizable based on application.
SPI flash	16 MB flash connected via the SPI interface.
ESP32-P4	High-performance MCU with large internal memory; supports advanced image and voice processing.
Battery Connector	Connects to a lithium battery.
Reset Button	Resets the board. Marked with  on the enclosure.
Boot Button	Controls boot mode. Marked with  on the enclosure. Press the Reset Button while holding down the Boot Button to reset ESP32-P4 and enter firmware download mode. Firmware can then be downloaded to SPI flash via the USB Debug Port. In general applications, it can act as a confirmation button.
Camera	2 MP resolution with manually adjustable focal length. For details, refer to Camera Datasheet .

Application Examples The following application examples are available for ESP32-P4-EYE:

- **Factory Demo** - Demonstrates a comprehensive mini camera application for ESP32-P4-EYE that supports photo capture, timed capture, video recording, album preview, USB SD card mounting, image parameter configuration, and AI features including face detection, pedestrian detection, and YOLOv11-nano-based object detection.

For more examples and the latest updates, please refer to the [examples](#) folder.

To explore the application examples or to develop your own, please follow the steps outlined in the [Application Development](#) section.

Application Development Before powering up your ESP32-P4-EYE, please make sure that it is in good condition with no obvious signs of damage.

Required Hardware

- ESP32-P4-EYE
- USB cables
- Computer running Windows, Linux, or macOS

Note: Be sure to use a good quality USB cable. Some cables are for charging only and do not provide the needed data lines nor work for programming the boards.

Optional Hardware

- MicroSD card
- Lithium battery

Hardware Setup Connect ESP32-P4-EYE to your computer using a USB cable. The board can be powered through the USB 2.0 Device Port or USB Debug Port. The USB Debug Port is recommended for flashing firmware and debugging.

Software Setup To set up your development environment and flash an application example onto your board, please follow the [installation instructions](#) in [ESP-IDF Get Started](#).

Hardware Reference

Functional Block Diagram The block diagram below shows the components of ESP32-P4-EYE and their inter-connections.




Fig. 17: ESP32-P4-EYE Functional Block Diagram (click to enlarge)

Power Supply Options ESP32-P4-EYE can be powered using the following methods:

1. Via the `USB 2.0 Device Port` or `USB Debug Port`

Connect ESP32-P4-EYE to a power source using a USB Type-C cable through either of the two ports. If a lithium battery is already installed, it will be charged simultaneously.

2. Via the `Battery Connector`

To use this method, first open the enclosure, then connect the battery to the Battery Connector. The lithium battery must not exceed 4 mm × 25 mm × 45 mm in size. It should use a 1.25 mm pitch connector, and the polarity must match the markings on the PCB.

Female Header

USB 2.0 Device Port Circuit

LCD Circuit Please note that this interface supports SPI displays. ESP32-P4-EYE features the [ST7789](#), which uses the `LCD_BL` pin (`GPIO20`) to control the backlight.




Fig. 18: Battery Connection (click to enlarge)



Fig. 19: Female Header (click to enlarge)


USB HighSpeed & Power in:

Fig. 20: USB 2.0 Device Port Circuit (click to enlarge)


1.54 INCH LCD:

Fig. 21: LCD Circuit (click to enlarge)

MicroSD Card:




Fig. 22: MicroSD Card Slot Interface Circuit (click to enlarge)

MicroSD Card Slot Interface Circuit Please note that the MicroSD card interface supports:

- 1-bit and 4-bit SD bus configurations
- Communication via SDIO protocol or SPI protocol

Charging Circuit

Microphone Circuit

Camera Circuit

Rotary Encoder Circuit

ESP32-C6-MINI-1U Module Circuit

Hardware Revision Details

No previous versions available.

Related Documents

Please download the following documents from [the HTML version of esp-dev-kits Documentation](#).

- [ESP32-P4-EYE Schematic](#) (PDF)
- [ESP32-P4-EYE PCB Layout](#) (PDF)
- [Camera Datasheet](#) (PDF)
- [Display Datasheet](#) (PDF)
- [ST7789VW Datasheet](#) (PDF)




Fig. 23: Charging Circuit (click to enlarge)

DMIC




Fig. 24: Microphone Circuit (click to enlarge)

Camera Connector:

I2C LevelShift:




Fig. 25: Camera Circuit (click to enlarge)




Fig. 26: Rotary Encoder Circuit (click to enlarge)





Fig. 27: ESP32-C6-MINI-1U Module Circuit (click to enlarge)

- [OV2710 Overview \(PDF\)](#)

Table 3: ESP32-P4 Development Boards



Chapter 4

Related Documentation and Resources

4.1 Developer Zone

- [ESP-IDF Programming Guide for ESP32-P4](#) –Extensive documentation for the ESP-IDF development framework.
- [ESP-IoT-Solution Programming Guide](#) - Extensive documentation for the ESP-IoT-Solution development framework.
- [ESP-FAQ](#) - A summary document of frequently asked questions released by Espressif.
- ESP-IDF and other development frameworks on GitHub.
<https://github.com/espressif>
- ESP32 BBS Forum –Engineer-to-Engineer (E2E) Community for Espressif products where you can post questions, share knowledge, explore ideas, and help solve problems with fellow engineers.
<https://esp32.com/>
- The ESP Journal –Best Practices, Articles, and Notes from Espressif folks.
<https://blog.espressif.com/>
- See the tabs SDKs and Demos, Apps, Tools, AT Firmware.
<https://espressif.com/en/support/download/sdks-demos>

4.2 Products

- ESP32-P4 Series SoCs –Browse through all ESP32-P4 SoCs.
<https://espressif.com/en/products/socs?id=ESP32-P4>
- ESP32-P4 Series Modules –Browse through all ESP32-P4-based modules.
<https://espressif.com/en/products/modules?id=ESP32-P4>
- ESP32-P4 Series DevKits –Browse through all ESP32-P4-based devkits.
<https://espressif.com/en/products/devkits?id=ESP32-P4>
- ESP Product Selector –Find an Espressif hardware product suitable for your needs by comparing or applying filters.
<https://products.espressif.com/#/product-selector>

4.3 Contact Us

- See the tabs Sales Questions, Technical Enquiries, Circuit Schematic & PCB Design Review, Get Samples (Online stores), Become Our Supplier, Comments & Suggestions.
<https://espressif.com/en/contact-us/sales-questions>

Chapter 5

Disclaimer and Copyright Notice

Information in this document, including URL references, is subject to change without notice.

All third party's information in this document is provided as is with no warranties to its authenticity and accuracy.

No warranty is provided to this document for its merchantability, non-infringement, fitness for any particular purpose, nor does any warranty otherwise arising out of any proposal, specification or sample.

All liability, including liability for infringement of any proprietary rights, relating to use of information in this document is disclaimed. No licenses express or implied, by estoppel or otherwise, to any intellectual property rights are granted herein.

The Wi-Fi Alliance Member logo is a trademark of the Wi-Fi Alliance. The Bluetooth logo is a registered trademark of Bluetooth SIG.

All trade names, trademarks and registered trademarks mentioned in this document are property of their respective owners, and are hereby acknowledged.