



DIN Rail Power Supply

From The World's No.1 Power Supply Company

October 2018



www.DeltaPSU.com



DIN Rail Power Supply

Product Introduction

CLiQ™



AR

- Universal AC input voltage range
- Power will not de-rate for the entire input voltage range
- Power Boost of 150% for 3 seconds (24V/480W: 200% for 2 seconds)
- Full corrosion resistant aluminium casing (except 12V/15W, 12V/30W, 24V/48W and 24V/60W)
- Conformal coating on PCBAs to protect against common dust and chemical pollutants (except DRP-24V48W1AZ and DRP024V060W1AZ)
- Hazardous Locations approval to ATEX and Class I, Div 2 for selected models

CLiQ^{II}



AR

- Universal AC input voltage range
- Power will not de-rate for the entire input voltage range
- Power Boost of 150% for 5 seconds (24V/480W: 200% for 2 seconds)
- Full corrosion resistant aluminium casing (except DRP024V060W1N□)
- Extreme low temperature cold start -40°C for selected models
- Conformal coating on PCBAs to protect against common dust and chemical pollutants
- Hazardous Locations approval to ATEX and Class I, Div 2 for selected models

CLiQ^{III}



AR

- Universal AC input voltage range
- Built-in constant current circuit for charging application
- Power Boost of 150% for 5 seconds
- SEMI F47 compliance at 120Vac
- Extreme low temperature cold start at -40°C
- Built-in DC OK Contact and LED indicator for DC OK
- Conformal coating on PCBA to protect against common dust and chemical pollutants


CLiQ^M



AR

- Universal AC input voltage range
- High power density in corrosion resistant aluminium casing
- Power Boost of 150% up to 7 seconds
- Advanced Power Boost (APB)
- DNV GL and ABS approvals for maritime applications
- Built-in DC OK contact and LED indicator for DC OK/ Over Load
- Conformal coating on PCBAs to protect against common dust and chemical pollutants

CLIQ^{VA}




- Universal AC input voltage range
- LCD display monitoring the output current / voltage / peak current and temperature
- Life time expectancy alarm signal and monitoring
- Power Boost of 150% up to 7 seconds
- Advanced Power Boost (APB)
- DC OK Contact and LED indicator for DC OK/ Overload
- Conformal coating on PCBAs to protect against common dust and chemical pollutants

LYTE




- Universal AC input voltage range
- High power density
- Built-in constant current circuit for reactive loads
- Built-in DC OK relay contact (option available)
- Compliance to SEMI F47 @ 200Vac
- 15kV common mode & 8kV differential mode ESD immunity
- Conformal coating on PCBAs to protect against common dust and chemical pollutants

CHROME



- Class II Double Isolation (No earth connection is required)
- Universal AC input voltage range and full power up to 55°C
- Power will not de-rate for the entire input voltage range
- Can be installed in compact cabinets
- NEC Class 2 and Limited Power Source (LPS) approvals (except DRG-12V100W1AZ)
- Conforms to harmonic current IEC/EN 61000-3-2, Class A
- Safety approval according to IEC/EN/UL 60950-1 (ITE standard) and UL 508 (Industrial standard)

sync



- Ultra compact size
- Universal AC input voltage range and full power from -10°C to 55°C operation
- Up to 89.0% efficiency
- Low earth leakage current < 0.5mA @ 264Vac
- Built-in DC OK relay contact option available
- Extreme low temperature cold start at -40°C
- NEC Class 2 / Limited Power Source (LPS) certified

DIN Rail Modules

Product Introduction

cliQ^{II}

Redundancy Modules



AR

- Wide input and output range of 22-60Vdc
- Very wide operating temperature from -40°C to +80°C
- Built-in 2 channel DC OK signal and alarm relay contact
- Support N+1 Redundancy connection
- Conformal coating on PCBAs to protect against common dust and chemical pollutants
- Hazardous Locations approval to ATEX and Class I, Div 2
- IP20 Certified

cliQ^{II}

Buffer Modules



AR

- Minimum buffering time of:
 - 250ms @ 24V/20A for DRB-24V020ABN
 - 200ms @ 24V/40A for DRB-24V040ABN
- Flexible operating buffering voltage modes:
 - Fixed mode at 22Vdc; Dynamic mode for $V_{in} - 1V$
- Support parallel connection to extend buffering time
- Conformal coating on PCBAs to protect against common dust and chemical pollutants
- Hazardous Locations approval to ATEX and Class I, Div 2 for DRB-24V020ABA

cliQ^{II}

DC-UPS Module



AR

- Full corrosion resistant aluminium casing
- Suitable for 24V system up to 40A
- Built-in diagnostic monitoring for DC OK, Discharge and Battery Fail by relay contacts
- LED indicator for DC OK, Battery Charging, Battery Discharging, Battery Fail and Battery Reverse Polarity
- High MTBF > 500,000 hrs per Telcordia SR-332
- Conformal coating on PCBAs to protect against common dust and chemical pollutants

CHROME

DC-UPS Module



AR

- Suitable for 24V system up to 10A
- Zero switch over time from loss of DC input to battery operation
- Built-in diagnostic monitoring for DC OK, Discharge and Battery Fail by relay contacts
- Full power for the entire temperature range from -20°C to +60°C
- LED indicator for DC OK, Battery Charging, Battery Discharging, Battery Fail and Battery Reverse Polarity
- High MTBF > 500,000 hrs as per Telcordia SR-332

DIN Rail Power Supply & Modules

Product List

New products are frequently introduced. Please visit www.DeltaPSU.com for latest product updates.

Series	Model Name	Phase			PFC	Output Voltage	Output Current	Output Power	Input Voltage Range*	Dimensions (L x W x D)
		1	2	3						
CliQ	DRP012V015W1AY	●				12V	1.25A	15W	85-264Vac (DC input range 120-375Vdc)	100 x 32 x 100.6 mm (3.94" x 1.26" x 3.96")
	DRP012V015W1AZ	●								
	DRP012V030W1AY	●					2.5A	30W		100 x 32 x 100.6 mm (3.94" x 1.26" x 3.96")
	DRP012V030W1AZ	●								121 x 32 x 120 mm (4.76" x 1.26" x 4.72")
	DRP012V060W1AA	●					5.0A	60W		121 x 50 x 118.7 mm (4.76" x 1.97" x 4.67")
	DRP012V100W1AA	●					8.33A	100W		
	DRP-24V48W1AZ	●				24V	2.0A	48W	85-264Vac (DC input range 120-375Vdc)	100 x 32 x 100.6 mm (3.94" x 1.26" x 3.96")
	DRP024V060W1AZ	●					2.5A	60W		120.6 x 32 x 113 mm (4.75" x 1.26" x 4.45")
	DRP024V060W1AA	●					2.5A	60W		121 x 32 x 120 mm (4.76" x 1.26" x 4.72")
	DRP024V120W1AA	●			●		5.0A	120W		121 x 50 x 118.7 mm (4.76" x 1.97" x 4.67")
	DRP024V240W1AA	●			●		10.0A	240W		121 x 85 x 118.5 mm (4.76" x 3.35" x 4.67")
	DRP024V480W1AA	●			●		20.0A	480W		121 x 160 x 118.5 mm (4.76" x 6.30" x 4.67")
CliQ II	DRP024V060W1BA	●				24V	2.5A	60W	85-264Vac (DC input range 120-375Vdc)	121 x 32 x 125 mm (4.76" x 1.26" x 4.92")
	DRP024V060W1BN	●								
	DRP024V060W1NY	●					2.5A	60W		120.6 x 32 x 119.3 mm (4.75" x 1.26" x 4.70")
	DRP024V060W1NZ	●								
	DRP-24V100W1NN	●			●		3.8A	91.2W		124 x 40 x 124 mm (4.88" x 1.57" x 4.88")
	DRP024V120W1BA	●					5.0A	120W		121 x 50 x 123.1 mm (4.76" x 1.97" x 4.85")
	DRP024V120W1BN	●								
	DRP024V240W1BA	●			●		10.0A	240W		121 x 85 x 124.1 mm (4.76" x 3.35" x 4.89")
	DRP024V240W1BN	●			●					
	DRP024V480W1BA	●			●		20.0A	480W		121 x 144 x 118.6 mm (4.76" x 5.67" x 4.67")
	DRP024V480W1BN	●			●					
	DRP-24V120W2BN	●	●				5.0A	120W	2 x 180-550Vac or 180-305Vac (Single Phase) (DC input range 254-780Vdc)	124 x 40 x 117 mm (4.88" x 1.57" x 4.61")
	DRP-24V240W2BN	●	●		●		10.0A	240W		124 x 60 x 117 mm (4.88" x 2.36" x 4.61")
	DRP024V060W3BA		●	●			2.5A	60W	3 x 320-600Vac or 2 x 360-600Vac (DC input range 450-800Vdc) For 960W: 3 x 320-600Vac or 2 x 380-600Vac (DC input range 450-800Vdc)	121 x 50 x 117.3 mm (4.76" x 1.97" x 4.62")
	DRP024V060W3BN		●	●						
	DRP024V120W3BA		●	●			5.0A	120W		121 x 50 x 117.3 mm (4.76" x 1.97" x 4.62")
	DRP024V120W3BN		●	●						
	DRP024V240W3BA		●	●			10.0A	240W		121 x 70 x 117.3 mm (4.76" x 2.76" x 4.62")
	DRP024V240W3BN		●	●						
	DRP024V480W3BA		●	●	●		20.0A	480W		121 x 140 x 117.3 mm (4.76" x 5.51" x 4.62")
	DRP024V480W3BN		●	●	●					
	DRP024V960W3BN		●	●	●		40.0A	960W		121 x 255 x 117.3 mm (4.76" x 10.0" x 4.62")
	DRP048V060W1BA	●				48V	1.25A	60W	85-264Vac (DC input range 120-375Vdc)	121 x 32 x 125 mm (4.76" x 1.26" x 4.92")
	DRP048V060W1BN	●								
	DRP048V120W1BA	●			●		2.5A	120W		121 x 50 x 123.1 mm (4.76" x 1.97" x 4.85")
	DRP048V120W1BN	●			●					
	DRP048V240W1BA	●			●		5.0A	240W		121 x 85 x 124.1 mm (4.76" x 3.35" x 4.86")
	DRP048V240W1BN	●			●					
	DRP048V480W1BA	●			●		10.0A	480W		121 x 144 x 118.6 mm (4.76" x 5.67" x 4.67")
	DRP048V480W1BN	●			●					

*DC input is certified for selected models.

Model Numbering

DR	P	□V	□W	□	□	□
DIN Rail	Product Type P - Power Supply	Output Voltage	Output Power	Phase Input 1 - Single Phase 2 - Two Phase 3 - Three Phase	A - CliQ Series B - CliQ II Series N - NEC Class 2	A - Metal Case, with Class I, Div 2 and ATEX approvals N - Metal Case, without Class I, Div 2 and ATEX approvals Y - Plastic Case, with Class I, Div 2 and ATEX approvals Z - Plastic Case, without Class I, Div 2 and ATEX approvals

Series	Model Name	Phase			PFC	Output Voltage	Output Current	Output Power	Input Voltage Range*	Dimensions (L x W x D)
		1	2	3						
CliQ III	DRP-24V120W1CAN	●			●	24V	5.0A	120W	88-264Vac	124 x 40 x 117 mm (4.88" x 1.57" x 4.60")
	DRP-24V120W1CBN	●			●				88-264Vac (DC input range 88-375Vdc)	
	DRP-24V240W1CAN	●			●		10.0A	240W	88-264Vac	124 x 60 x 117 mm (4.88" x 2.36" x 4.60")
	DRP-24V240W1CBN	●			●				88-264Vac (DC input range 88-375Vdc)	
	DRP-24V480W1CAN	●			●		20.0A	480W	88-264Vac	124 x 82 x 127 mm (4.88" x 3.23" x 5.00")
	DRP-24V480W1CBN	●			●				88-264Vac (DC input range 88-375Vdc)	
CliQ M	DRM-24V80W1PN	●			●	24V	3.4A	81.6W	85-276Vac (DC input range 88-375Vdc)	124 x 32 x 102 mm (4.88" x 1.26" x 4.02")
	DRM-24V120W1PN	●			●		5.0A	120W	85-264Vac (DC input range 88-375Vdc)	124 x 40 x 117 mm (4.88" x 1.57" x 4.61")
	DRM-24V240W1PN	●			●		10.0A	240W	85-276Vac (DC input range 88-375Vdc)	124 x 60 x 117 mm (4.88" x 2.36" x 4.61")
	DRM-24V480W1PN	●			●		20.0A	480W		124 x 82 x 127 mm (4.88" x 3.23" x 5.00")
	DRM-24V960W1PN	●			●		40.0A	960W	85-264Vac	124 x 125 x 133.6 mm (4.88" x 4.92" x 5.26")
CliQ VA	DRV-24V120W1PN	●			●	24V	5.0A	120W	85-264Vac	124 x 60 x139 mm (4.88" x 2.36" x 5.47")
	DRV-24V240W1PN	●			●		10.0A	240W	85-276Vac	124 x 60 x139 mm (4.88" x 2.36" x 5.47")
	DRV-24V480W1PN	●			●		20.0A	480W		124 x 82 x149 mm (4.88" x 3.23" x 5.87")
Lyte	DRL-24V120W1A□	●				24V	5.0A	120W	85-264Vac	123.6 x 40 x 117.6 mm (4.87" x 1.57" x 4.63")
	DRL-24V240W1A□	●			●		10.0A	240W		123.6 x 60 x 117.6 mm (4.87" x 2.36" x 4.63")
	DRL-24V480W1A□	●			●		20.0A	480W		123.6 x 85.5 x 128.5 mm (4.87" x 3.37" x 5.06")
	DRL-48V120W1A□	●				48V	2.5A	120W	85-264Vac	123.6 x 40 x 117.6 mm (4.87" x 1.57" x 4.63")
Chrome	DRC-5V10W1A□	●				5V	1.5A	7.5W	90-264Vac	91 x 18 x 55.6 mm (3.58" x 0.71" x 2.19")
	DRC-12V10W1A□	●				12V	0.83A	10W	90-264Vac	91 x 18 x 55.6 mm (3.58" x 0.71" x 2.19")
	DRC-12V30W1A□	●					2.1A	25.2W		91 x 53 x 55.6 mm (3.58" x 2.09" x 2.19")
	DRC-12V60W1A□	●					4.5A	54W		91 x 71 x 55.6 mm (3.58" x 2.80" x 2.19")
	DRC-12V100W1AZ	●					6.0A	72W		91 x 89.9 x 55.6 mm (3.58" x 3.54" x 2.19")
	DRC-24V10W1A□	●				24V	0.42A	10W	90-264Vac	91 x 18 x 55.6 mm (3.58" x 0.71" x 2.19")
	DRC-24V10W1HZ	●					0.42A	10W		91 x 18 x 55.6 mm (3.58" x 0.71" x 2.19")
	DRC-24V30W1A□	●					1.25A	30W		91 x 53 x 55.6 mm (3.58" x 2.09" x 2.19")
	DRC-24V60W1A□	●					2.5A	60W		91 x 71 x 55.6 mm (3.58" x 2.80" x 2.19")
	DRC-24V100W1A□	●					3.8A	91.2W	90-264Vac (DC input range 120-375Vdc)	91 x 89.9 x 55.6 mm (3.58" x 3.54" x 2.19")

*DC input is certified for selected models.

Model Numbering

DR	P –	□V	□W	1	C	□	N
DIN Rail	Product Type P - Power Supply	Output Voltage	Output Power	Phase Input 1 - Single Phase	C - CliQ III Series	Input Voltage A - AC Input B - AC & DC Input	N - Metal Case, without Class I, Div 2 and ATEX approvals

DR	M –	□V	□W	1	P	N
DIN Rail	Product Series M - CliQ M Series	Output Voltage	Output Power	Phase Input 1 - Single Phase	Advanced Power Boost (APB)	N - Metal Case, without Class I, Div 2 and ATEX approvals

DR	V –	□V	□W	1	P	N
DIN Rail	Product Series VA - CliQ VA Series	Output Voltage	Output Power	Phase Input 1 - Single Phase	Advanced Power Boost (APB)	N - Metal Case, without Class I, Div 2 and ATEX approvals

Series	Model Name	Phase		PFC	Output Voltage	Output Current	Output Power	Input Voltage Range*	Dimensions (L x W x D)
		1	2						
Sync	DRS-5V30W1NZ	●			5V	3.0A	15W	85-264Vac (DC input range 120-375Vdc)	75 x 21 x 89.5 mm (2.95" x 0.83" x 3.52")
	DRS-5V50W1A□	●				6.0A	30W		75 x 30 x 89.5 mm (2.95" x 1.18" x 3.52")
	DRS-5V50W1N□	●				5.0A	25W		75 x 30 x 89.5 mm (2.95" x 1.18" x 3.52")
	DRS-12V50W1N□	●			12V	4.0A	48W	85-264Vac (DC input range 120-375Vdc)	75 x 30 x 89.5 mm (2.95" x 1.18" x 3.52")
	DRS-24V30W1AZ	●			24V	1.25A	30W	85-264Vac (DC input range 120-375Vdc)	75 x 21 x 89.5 mm (2.95" x 0.83" x 3.52")
	DRS-24V30W1NZ	●				1.25A	30W		75 x 21 x 89.5 mm (2.95" x 0.83" x 3.52")
	DRS-24V50W1N□	●				2.1A	50W		75 x 30 x 89.5 mm (2.95" x 1.18" x 3.52")
	DRS-24V100W1A□	●		●		4.0A	96W		75 x 45 x 100 mm (2.95" x 1.77" x 3.94")
	DRS-24V100W1N□	●		●		3.8A	91.2W		75 x 45 x 100 mm (2.95" x 1.77" x 3.94")

* DC input is certified for selected models.

Series	Product Type	Model Name	Output Voltage	Output Current	Input Current	Input Voltage Range	Dimensions (L x W x D)
CliQ II	Redundancy Module	DRR-20A	22-60V	20.0A	(1+1 Redundancy) = Nominal 2 x 12.5A (N+1 Redundancy) = Nominal 2 x 10A	22-60Vdc	121 x 50 x 122.1 mm (4.76" x 1.97" x 4.81")
		DRR-20N					
		DRR-40A			(1+1 Redundancy) = Nominal 2 x 25A (N+1 Redundancy) = Nominal 2 x 20A		
		DRR-40N					
	Buffer Module	DRB-24V020ABA	24V	20.0A	Charging Mode: < 0.6A	22.8-28.8Vdc	121 x 70 x 120.1 mm (4.76" x 2.76" x 4.73")
		DRB-24V020ABN					
		DRB-24V040ABN			Charging Mode: < 0.6A		
Chrome	DC-UPS Module	DRU-24V40ABN	24V	40.0A	Charging Mode: 2.0A ± 1.0A	24-28Vdc	121 x 50 x 117.3 mm (4.76" x 1.97" x 4.62")
		DRU-24V10ACZ		10.0A	Charging Mode: 0.5A ± 0.1A		91 x 71 x 55.6 mm (3.58" x 2.80" x 2.19")

Model Numbering

DR	L –	□V	□W	1	A	□
DIN Rail	Product Series L - Lyte Series	Output Voltage	Output Power	Phase Input 1 - Single Phase	Standard Bracket	A - Without DC OK Relay Contact S - With DC OK Relay Contact
DR	C –	□V	□W	1	□	□
DIN Rail	Product Type C - Isolation Class II Power Supply	Output Voltage	Output Power	Phase Input 1 - Single Phase	A - No PFC H - Household Approval	Z - Black Plastic Case G - Grey Plastic Case C - Black Plastic Case with conformal coating ¹⁾
1) Options for DRC-24V60W1A□ and DRC-24V100W1A□ only						
DR	S –	□V	□W	1	□	□
DIN Rail	Product Series S - Sync Series	Output Voltage	Output Power	Phase Input 1 - Single Phase	A - Non NEC Class 2 N - NEC Class 2	Z - Without DC OK Relay Contact R - With DC OK Relay Contact
DR	R –			□	□	
DIN Rail	Product Type R - Redundancy Module			Output Current 20 - 20A 40 - 40A	A - Metal Case, with Class I, Div 2 N - Metal Case, without Class I, Div 2	
DR	□ –	24V	□A	□	□	
DIN Rail	Product Type U - DC-UPS Module B - Buffer Module	Output Voltage	Output Current	B - CliQ II Series C - Chrome Series	A - Metal Case, with Class I, Div 2 N - Metal Case, without Class I, Div 2 Z - Plastic Case, without Class I, Div 2	



To learn more about DIN rail power supply, please visit our website.





ASIA

Delta Electronics, Inc.

3 Tungyuan Road, Chungli Industrial Zone,
Taoyuan County 32063, Taiwan, R.O.C

Tel: +886 3 452 6107

Fax: +886 3 434 3617

Delta Electronics (Shanghai) Co., Ltd. Headquarters

No. 182 Minyu Road, Pudong,
Shanghai, P.R.C. 201209

Tel: +86 21 68723988

Fax: +86 21 68723996

Delta Electronics (Shanghai) Co., Ltd. Beijing Branch

No. 7 Building, 6th Courtyard, Beichen East Rd.,
Chaoyang Dist., Beijing, P.R.C. 100105

Tel: +86 10 82253225

Fax: +86 10 82251360

Delta Electronics (Thailand) PCL.

909 Soi 9, Moo 4, Bangpoo Industrial Estate
(E.P.Z.), Pattana 1 Rd., T. Phrakasa, A. Muang,
Samutprakarn 10280, Thailand

Tel: +662 709 2800

Fax: +662 709 2827

Delta India Electronics Pvt. Ltd.

Plot No. 43, Sector - 35, HSIIDC,
Gurgaon, Haryana 122001

Tel: +91 124 4874900

+91 124 4169040

Fax: +91 124 4874945

Delta Electronics (Japan), Inc.

2-1-14 Shibadaimon, Minato-Ku,
Tokyo, 105-0012, Japan

Tel: +81 3 5733 1155

Fax: +81 3 5733 1255

Delta Electronics (Korea), Inc.

1511, Byucksan Digital Valley 6-Cha,
Gasam-dong, Geumcheon-gu,
Seoul, 153-704, Korea

Tel: +82 2 515 5303

+82 2 515 5305

Fax: +82 2 515 5302

NORTH AMERICA

Delta Products Corporation North American Headquarters

46101 Fremont Blvd.

Fremont, CA 94538, U.S.A.

Tel: +1 510 668 5100

CENTRAL AND SOUTH AMERICA

Delta Greentech (Brasil) S.A.

Rua Itapeva, 26 - 3º, andar Edifício Itapeva,
One - Bela Vista 01332-000 - São Paulo - SP -
Brasil

Tel: +55 11 3568 3850

Fax: +55 11 3568 3865

Delta Electronics International Mexico, S.A. de C.V.

Via Dr. Gustavo Baz No. 2160,
Fracc. Ind. La Loma, Tlalnepantla de Baz,
Estado de México, 54060, Mexico

Tel: +52 55 2628 3015

EUROPE

Delta Electronics (Netherlands) B.V. EMEA Headquarters

Zandsteen 15

2132 MZ Hoofddorp, The Netherlands

Tel: +31 20 655 0975

Fax: +31 20 655 0999

De Witbogt 20

5652 AG Eindhoven, The Netherlands

Tel: +31 40 800 3878

Fax: +31 40 800 3898

Authorized Distributor:

www.DeltaPSU.com | info@deltapsu.com

October 2018 - All information and specifications are subjected to change without prior notice.