

INTRODUCING HIGH-DENSITY BNC CONNECTORS

- Designed to improve panel density - up to 4x the panel density of standard BNC connectors
- Optimized for 12G-SDI broadcast video solutions
- Fits traditional broadcast cables



High-density BNC connectors from TE Connectivity (TE) provide a compact design solution for large video transmission systems, broadcast systems, and video signal applications. High-density BNC connectors are smaller than traditional BNC connectors and are intended to be arranged in tighter configurations than traditional BNC connectors, allowing for up to four times as many interconnects in the same footprint.

APPLICATIONS

- Large video transmission systems
 - Surveillance cameras / smart city surveillance system
- Broadcast equipment
 - SDI input & output video cards
 - Studio and broadcast cameras
- Digital Video - UHD TV 4K and 8K
- Instrumentation
 - PXI (PCI extensions for instrumentation)
- Industrial equipment
 - 3D Automated optical inspection (3D AOI)
 - Machine vision / industrial cameras
 - Frame grabbers
- Military systems
 - Unmanned aerial vehicle (UAV)

KEY BENEFITS

- High-density BNC connectors are smaller than traditional BNC connectors and are intended to be arranged in tighter configurations than traditional BNC connectors, allowing for up to four times as many interconnects in the same footprint
- Using a customized insertion/extraction tool (2446195-1), cable assemblies can be connected and disconnected to receptacles mounted on the panel utilizing a bayonet-style mounting interface even when space is limited
- Developed for 12G-SDI Ultra HD video, machine vision applications and designed for CoaXPress 2.0 and SMPTE ST 2082 standards
- Lock washer and nut included for use in high vibration applications

PRODUCT FEATURES

- Up to 75-ohm performance
- Designed to improve panel density - up to 4x the panel density of standard BNC connectors
- Fit traditional broadcast cables
- 20% lighter than standard BNC connectors
- 51% smaller than standard BNC connectors and 39% smaller than mini-BNC connectors.
- Quarter turn bayonet-style coupling design includes locking feature
- Quicker, easier connector installation and removal in limited space
- Optimized for 12G-SDI broadcast video solutions
- Designed for CoaXPress 2.0 and SMPTE ST 2082 standards
- DC-12 GHz connector frequency range
- IP67 waterproof panel connector available

LEARN MORE

- [Landing Page](#)
- [Brochure](#)
- [Parts List](#)