



90 Series



0.290" (7.37mm) LED Panel Mount Indicator Cartridge, Bi-Pin and Wire Leads Termination Styles

The 90 Series LED panel mount indicators offer superior construction, longer life and watertight socket options for splashdown environments. Available with cartridge, bi-pin and wire leads termination styles for use with spring retainer clip, socket holder or wiring plugs.



Termination

[Cartridge, Bi-pin, Wire Leads](#)

Available with a variety of LEDs including AlInGaP and InGaN technology for high brightness applications, bi-color and with integrated resistors.

LED Position

[Prominent Indicator](#)

Designed for quick installation in display panels and reduces overall cost due to less-frequent replacements.

Single LED

[Red, Green, White, Blue, Amber, Orange](#)

Cartridge, bi-pin and wire leads termination styles for use with spring retainer clip, socket holder or wiring plugs

Bi-Color LED

[Red/Green](#)

Offered with a variety of lens options: cylindrical, flush, dome, wide cylindrical or wide flush all featured with fresnel pattern lens which provide excellent light focus and assure maximum light output.

Fresnel Pattern Lens (optional)

[Cylindrical, Flush, Dome](#)

Spring retainer clip secures uniform placement of the indicator to the panel and is ideal for high vibration environments.


Related Voltage

[2 to 60 VDC, 120VAC](#)

Watertight socket options for splashdown environments

Compliance

[RoHS, REACH](#)




BRIGHT LED




LED COLOR OPTIONS



MOUNTING HOLE Ø 0.290"



LENS OPTIONS



AC/DC VOLTAGE



WATER TIGHT

Product Specification

- Prominent LED panel mount indicator
- Panel hole diameter: 0.290" (7.37mm)
- Built-in LED can be used DC circuits (2 to 60 VDC) or 120VAC circuits
- Terminal styles: cartridge, bi-pin and wire leads
- Offered with a variety of LEDs
- Single color: red, green, white, blue, amber, and orange
- Bi-color: red/green
- Seven lens colors available: red, amber, yellow, green, blue, water clear and smoke

- Available with: no lens, cylindrical lens, flush lens or dome lens
- Black bezel offering to enhance LED contrast
- Mounting hardware provided (spring retainer clip and washer)
- Watertight socket options for splashdown environments
- For use with socket holder (PS90 or PS90T; sold separately) or wiring plug (SH90 or CSH90; sold separately)
- Compliant with RoHS and REACH requirements

Applications



Transportation





Industrial Control Display



Aircraft



Variations


 905
No
Lens

 91
Cylindrical
Lens

 94
Flush
Lens

 96
Dome
Lens

 961
Wide
Cylindrical
Lens

 964
Wide
Flush
Lens

 PS90 /
PS90T
Socket
Holder

 SH90/
CSH90
Wiring
Plug

* see 90 Series data sheet for technical details and specific part numbers

Are you ready for next level illuminated components?